ROTHENBERGER

Quality since 1949



Soldering & Brazing
Welding
Industrial gases
Heating and Flaming
Camping
Garden & Household
Sanitary installation
Heating
Measure, test & inspect
Hand- and special tools











The customer guidance system that appears on our sales packaging


The ROTHENBERGER Industrial customer guidance system combines packaging, catalogue, "Lötfibel" and "Lötnavigator". These are precisely tailored to your needs and actively support your buying.

The clear colour coding of our gas appliances and solder makes it easy for you to put together your optimal working equipment.

The individual methods are characterised by the following colours or pictograms:







Should you have any questions, please contact our Customer Service: info-diy@rothenberger.com.

Only through your feedback can we succeed and become even better.

Safety advice for protection at work

- Safety glasses/welding shield, and depending on the tech
 - nology used, light protection qlasses

place

- Fireproof work pad Protective aloves
- Clean, protective working clothing, sturdy footwear
- Good ventilation of the work- Clear the workplace of flammable materials
- Get specific fire-extinguishing of work: water-based or powder-based fire extinguishers,
- workplace thoroughly to avoid After finishing soldering or welding, always check the smouldering fires water, etc.

operating manuals and safety

instructions

or welding always read and Before beginning soldering follow the manufacturer's

Possible causes of poor results

- Insufficient heat supply: solder Wrong solder and / or flux agents, depending on the type
- doesn't flow or does not cover heat too high: solder and / or flux burns or evaporates (formation of drops)
- soldering gap too big: no capillary effect (the solder cannot close the dab)
- been cleaned: oxide layer on the pipe ends and fittings have not surface of the workpiece

Never solder or weld tanks because of the high risk of explosion! Do not climb on

tanks: high risk of asphyxiation or poisoning!

This type of work must be carried out by a professional!

Defective electronic components after soldering: use temperature controlled Soldering Equipment (Elektroniklötstation)

ROTHENBERGER INDUSTRIAL

| | Pipe joints | | | surrace Joints | | soldering of electronic components |
|---|---|---|--|--|---|--|
| Soldering 🌢 | Brazing 🦶 | Gas welding 666 | Soldering 🔥 | Brazing 🐪 | Gas welding 🁭 | Soldering 🔥 |
| | | | 1. Preparation | | | |
| Cut the pipe with | Cut the pipe with a stable pipe cutter or saw perpendicular to the tube axis | ır to the tube axis | Cut the v | Cut the workpieces, deburr or chamfer the cut surfaces. | urfaces. | Cutting and stripping the cable ends. Preparing and equipping circuit boards. |
| After the cut, carefully deburr the pipe ends inside (using the correct tool both inside and outside). After deburring, remove any metal filings and accurately size the pipe ends. | ends inside (using the correct tool both emove any metal filings and accurately ipe ends. | On the conference of the state | Mechanically clean the joints of any oxidation layer (Cleaning pad, etc.) | oxidation layer (Cleaning pad, etc.) | Degrease and remove rust from the workpiece weld seam area. | المدافقين |
| Clean the soldering surfaces of the pipe ends and the fittings/expanded pipes with RoViles (metal-free cleaning pad) or special cleaning brushes until bare metal. | Clean the soldering surfaces of the pipe ends and the fittings/expanded pipes with RoVlies (metal-free cleaning pad) or special cleaning brushes until bare metal. | Debut, channer and its the pipe ends. | | Fasten the workpieces. | | rositori and ix the components. |
| Apply flux or soldering paste evenly on the pipe ends, in compliance with the legal guidelines. Brazing of drinking water pipes is permitted from 28 mm. It is necessary to use specially approved solders, fluxes and solder pastes. | Apply flux or soldering paste evenly on the pipe ends, in compliance with the legal guidelines. Brazing of drinking water pipes is permitted from 28 mm. It is necessary to use specially approved solders, fluxes and solder pastes. | Assemble the pipe ends. | Apply flux evenly on the soldering surfa | evenly on the soldering surfaces, if brazing, coat tip of rod in flux. | | Apply flux or soldering paste evenly on the soldering surfaces, respectively wetting the soldering wire and fitting/ |
| Wet the pipe and fitting/expanded pipes with flux while turning. Press together. | expanded pipes with flux while turning. Press together. | | | | Choice of an appropriate welding torch. | expanded pipe with flux while turning slowly. |
| Choice of an appropi | Choice of an appropriate soldering torch. | Choice of an appropriate welding torch. | Choice of an appropriate soldering torch. | iate soldering torch. | | Choice of the appropriate electric soldering equipment. |
| | | 2. Pr | 2. Procedures for soldering or welding | ding | | |
| Set the gas soldering machine so that there is a soldering machine so that there is a soldering wisible flame cone. | Set the gas soldering machine so that there is a soft neutral flame with a clearly visible flame cone. | Set the welding torch so that there is a neutral flame with a clearly visible flame cone. | Set the gas soldering machine so that there is a soft neutral flame with a clearly visible flame cone. | at there is a soft neutral flame with e flame cone. | Set the welding torch so that there is a neutral flame with a clearly visible flame cone. | - |
| Heat the soldering points evenly. | Heat soldering points evenly until the soldering point glows cherry red. | Heat the welding seam until the workpieces become molten. | Evenly heat the soldering areas. | Evenly heat the soldering areas. | Heat the welding seam until the workpieces become molten. | Heat the soldering area with the soldering tip and melt the solder on the soldering area |
| Once the soldering paste gleams silver, turn the flame away and fill the soldering gap with solder. | Melt the solder in the flame, until the soldering gap is filled. | Under constant heat supply melt the welding wire in the weld pool. | As soon as working temperature is reached, melt the solder on the workpiece. | Under constant heat supply melt the solder on the workpiece. | Under constant heat supply melt the welding wire in the weld pool. | |
| Let the soldering area cool down and rem with a damp cloth | Let the soldering area cool down and remove the residues of flux with a damp cloth. | Let the welding seam slowly cool down. | | | | Slowly let the soldering area cool down. |
| | Rinse pipelines. | | Let the soldering area cool down and remove the residues of flux. | and remove the residues of flux. | Slowly let the welding seam cool down. | Carefully and cautiously remove any |
| | Regularly perform leak tests. | | | | | sion on electronic components, circuit boards, etc. |
| | | | | | | |

The fundamentals of soldering technique

Working temperature:

this is the lowest surface temperature the solder melts and wets and binds ture and is limited through the flux where, with the materials to be joined, is determined by the working temperatogether the soldering area. Soldering temperature:

temperature of the solder.

from adhering oxidized parts both it's task is to clean the metal surfaces before and during the soldering. Flux composition relates specifically to the work pieces and the solder. Fluxes can be in paste, liquid or powder form, featuring various chemical compositions. temperature, respectively the melting

or different work pieces. Thus, the pending on the purpose, soft or hard it's job is to bind together two similar composition / alloy of the solder must be appropriate to the work pieces. Desolders can be used.

ing to add additional fluxes. these are fluxes which are added to the soldering areas are thinly coated solder components for specific uses. With these ready-made flux pastes and when the working temperature is reached, they are wetted all over with solder.

these are brazing, where the soldering rod is coated with a specific flux. These solders can be used without additional Flux-coated solders: fluxes. these can be soldering or brazing fluxes. They can be used without havwhich are already filled with specific

Flux-filled solders:

Flux pastes:

this is the heat source. There are soldering devices with open flame (resistance brazing device, electric (cartridge and gas powered soldering torches, etc.) and without flame soldering iron, or soldering guns, etc.).

Soldering devices:

The small soldering manual. Introduction to soldering and welding

techniques

is higher in brazing. With these solder-Soldering procedures can be divided into soldering and brazing, which features a different working temperature, which ing techniques, metallic materials, which can be either the same or different, are solidly joined together firmly with heat using a soldering torches and supplying a non-ferrous metal alloy, solder and a specific flux. Appropriately prepared material surfaces connected at their su solder. Thus, the m solder is alwavs low of the base materi supplying heat enou solder again, alway points of the base dering, connected

result in no or only minor changes to the arc welding / shielding gas welding), the forms a structural link with the molten Basically, soldering processes feature relatively low levels of working, which at the junction is melted by heating and can easily get their original shape back. easy handling, short working times and quality of the workpiece material itself When welding, (oxyacetylene welding / metallic material of the base workpieces

Norking temperature: < 450°C Low working temperature

Soldering 🐧

- Easy handling
- Short working time
- Almost no change in the quality of the
- - Combination of different materials possible Suitable for soldering electronic joints
- Easy desoldering through heat supply

Combination of different materials possible High mechanical and thermal stability Working temperature: > 450-1.100°C Easy handling

- of brazed joints
 - Easy desoldering through heat supply

Working temperature: > 1250°C Gas welding 000

Procedure

Brazing 0

- Very high working temperatures
- Very high mechanical and thermal strength of the welded joints
 - Structural connection by fusion of the workpieces

| Perfect soldering equipment in just a few easy steps with the soldering navigator | Perfect soldering equipment in just a few easy steps with soldering navigator |
|---|---|
| been a proven technique for joining workpieces together for many centuries! | leat enough heat to meit the n, always be separated, and |
| | he base materials. By de-sol- nnected workpieces can, by |
| | s, the melting range of the ways lower than the melting |
| electrode). | at their surface by the molten |
| e materials are wetted and additive (welding rod, rod electrode, wire | e materials are wetted and |

Roxy Kit Plus, Roxy Mapp, Roxy Universal, Roxy 400L, Three gas system Maxigas, Mapp Gas, Azetylen, Oxygen Welding and brazing powder Multigas, Maxigas, Mapp Gas Soldering iron, Guttering soldering set, Soldering station, Soldering gun, Soldering torch, Soldering Solder flux, Zinc soldering fluid, Salmiak stone Solder and Welding equipment torch with piezo, Hot Pack Set, RoFix Set Miniset, RoPen, Pocket Torch, Micropen, Not for Drinking water installations RoFill, Minigas, C200, Multigas 300, For drinking water installations Industrial gases Mapp Gas, Maxigas Flux

| 1 | Application/Connections | |
|--|--|---|
| 1 | Heading installations (copper pipelines) | Fittings Solder 3, soldering set |
| Pipe connections Power Fire | Drinking water installations (copper pipelines) | Fittings Solder 3, soldering set |
| | Gas pipelines (copper pipes for natural gas, butane and propane) | 1 |
| i : | Copper | Rod solders 1kg, Rolot 608 |
| Guttering, Linsmith works Guttering soldering set | Titan, Zinc | Rod solders 1kg, Rolot 608 |
| | Zinc | Standard solder, Rod solders 1kg, Rolot 608 |
| | Zinc | Standard solder |
| Metallic joints | Stainless steel | I |
| Power Fire Roxy machine | Aluminium | I |
| | non-ferrous metals (nickel, copper, brass, nickel alloy, zinc, tinplate) | Standard solder, Rod solders 1kg, Tiffany craft s |
| Electronic components | PCBs | Electronics solder, Radio solder, Electronic set |
| soldering station | cables/conductors/wires (copper) | Electronics solder, Radio solder, Electronic set |

Rolot 601, 602, 603, 605, 611, 612

Rolot 606, 607 Rolot 607, 610 Rolot 601, 602, 603

Rolot 601, 602, 603, 606, 607, 609, 610

t set

Rolot 606, 609 Rolot 606



With ROTHENBERGER Industrial tools you decide for high quality products made by ROTHENBERGER.

Our current range of soldering, welding, plumbing, measuring and hand tools and our equipment for outdoor, camping and household stands out an always innovative technology, powerful processing and high user-friendliness.

For more than 60 years, our family-owned business from Kelkheim has been a market-leading producer of technically advanced pipe tools, machinery and environmental technology, with customers in Germany and all over the globe.

We not only want to satisfy our customers, we want them to be excited.



Quality since 1949

ROTHENBERGER Industrial GmbH

Sodener Straße 47 65779 Kelkheim | Germany Tel. +49 (0) 6195 99 81 0 Fax +49 (0) 6195 99 81 79 10

Mail info-diy@rothenberger.com www.rothenberger-industrial.com

DSTR BUTOR

- Albania
- Belarus
- Andorra Armenia
- Azerbaijan
- Bosnia &

- Herzegovina
- Bulgaria
- Croatia
- Cyprus
- Republic
- Czech
- Denmark
- Georgia
- Greece
- Iceland
- Ireland Kosovo
- - Liechtenstein
 - Macedonia
- Malta Norway

Moldova

Monaco

Montenegro

- - Poland
 - Russia San Marino
- Serbia
- Slovakia
- Slovenia **Kingdom** Sweden

Ukraine

United



ROTHENBERGER INDUSTRIAL



The company

For more than 65 years, our family business based in Kelkheim, Germany, has been a leading manufacturer of technically sophisticated pipe tools, special equipment and environmental technology – going far beyond the borders of Germany. With more than 1,500 employees in over 50 group companies around the world, we produce and sell approximately 28 million ROTHENBERGER tools every year. Over 150 patents and trademarks, as well as the high level of in-house production ensures the quality of our products.

Based on the wide range of products required for the professional, ROTHENBERGER developed its user-friendly range of products for the professional handyman: ROTHENBERGER Industrial.

ROTHENBERGER Industrial GmbH was founded as a subsidiary of the ROTHENBERGER Group in 2007. Our young company stands for tradition, innovation and superior quality in the DIY/handyman market. This is reflected not only in the products but is also the basis of the corporate culture which defines ROTHENBERGER Industrial as a professional, competent and reliable partner.

With a presence in more than 3,500 professional and DIY stores, our products are available throughout Europe. Our target group of products offers a tailored portfolio of pipe and installation tools -ROTHENBERGER Industrial offers a balanced product assortment for the ambitious handyman. Our wide product range includes – in addition to traditional plumbing and hand tools – soldering and welding products, as well as outdoor, camping and metrology products. The continual maintenance of our product range, innovative packaging and attractively designed modules complement the professional performance program. The extensive distribution ensures the constant availability of our products. The close contact to our customers is one of the main reasons for our success.

Accordingly, our quality standards define our market presence with convenient packaging and well-presented displays in the market place.



The team

The ROTHENBERGER Industrial team consists of 35 employees, deployed across sales, purchasing, scheduling, shipping, storage, quality assurance and product management.

With our clear corporate structure, we live the seven values of the ROTHENBERGER group as part of the

large ROTHENBERGER family. This cohesion ensures a constant drive for motivation, passion, dedication and innovation creating the foundation of our business.

QUALITY, COMMITMENT and SERVICE are very important to us. Our team consists of highly trained, dedicated and skilled professionals.

Living the values

We see ourselves as a worldwide family that addresses new challenges with courage and entrepreneurial spirit, always clearly providing the demands and requirements of our products. We believe in quality, diligence, dynamism and respect and see these as guidelines for our business activities. For the purposes of this corporate philosophy, we have identified seven ROTHENBERGER basic values that underpin our work.

1 Cohesion as a family

We are part of the worldwide ROTHENBERGER family.



2 Trust

Our corporate culture is built on mutual trust, based on honest and transparent communication, continuous processes and fair cooperation.



3 Responsibility

We acknowledge our responsibility for results, resources, and for our own choices. Our commitment and our passion for our jobs leads to high customer and employee satisfaction.



4 Efficiency

We work efficiently, because we keep things simple.



5 Quality

We are concerned about the quality of employees, products and processes. Therefore, we demonstrate excellence in everything we do.



6 Courage

We have the courage to innovate and change things, even if this means that we must step out of our comfort zone.



7 Entrepreneurship

In our work, we engage with an entrepreneurial spirit, we are action-oriented, make quick decisions and never give up. We are ready for the future!




Main reasons


for choosing ROTHENBERGER Industrial

| 1 | Best prices and conditions for A grade quality products |
|----|--|
| 2 | Comprehensive price-performance relationship for distributors and end customers |
| 3 | Support for DIY stores through 26 ROTHENBERGER Industrial sales representatives in Germany and 4 in Austria |
| 4 | Quality! ROTHENBERGER Industrial ever uses high quality brass |
| 5 | ROTHENBERGER has been financially strong for over 65 years |
| 6 | Access to more product categories and innovations from the market leader |
| 7 | Access to ROTHENBERGER professional products for customer orders and any hire service |
| 8 | Supplier concentration for process cost optimisation |
| 9 | Colourful and informative self-service blister packaging |
| 10 | Proactive product streamlining |
| 11 | Professional and efficient modular development with consideration of capital commitment and transhipment |
| 12 | Significant participation of ROTHENBERGER Industrial project management in the standardisation of gas products on a European level |

YOU'LL FIND ROTHENBERGER WHEREVER YOU ARE



Visit our new, responsive mobile website





Learn all about our product portfolio (News, specifications etc.), latest events and other news about the company.


As an end user, locate your nearest ROTHENBERGER Industrial distributor.

As a distributor, our Login-area is available. Amongst other things, there is access to our image database and the archive of our Safety Data Sheets.

www.rothenberger-industrial.com

Contents

| Soldering and brazing | Camping, Garden & |
|-------------------------------|--------------------------------------|
| Soldering torches | Household |
| Brazing torches | Devices 61 |
| Solder | Lighters |
| Flux | Accessories 65 |
| Accessories 24 | |
| | Sanitary installation |
| Welding | Tube machining |
| Gas welding torches | Pipe cleaning |
| Arc Welders' | |
| Plastic Welders´ | Heating |
| Electrodes & gas welding wire | Heaters 83 |
| Accessories 40 | Accessories 87 |
| Industrial gases | Measure, test & inspect |
| Fuel gas | Building and wood moisture meters 89 |
| Helium | Distance measuring devices |
| Protective gas | Inspection devices 90 |
| Industrial oxygen | Temperature measuring devices 92 |
| Heating and flaming | Hand- and special tools |
| Flaming devices | • |
| Accessories 58 | Shears |
| | Pliers |
| | Special tools |
| | POS |
| | POS |



Soldering and brazing

Soldering equipment, Brazing equipment, Solder, **Flux and Accessories**

Welding

Electrodes & Gas welding wire, Accessories



Industrial gases

Fuel gas, Helium, Protective gas, Industrial oxygen

Heating and flaming

Flaming devices & Accessories





Sanitary installation

Tube machining & Pipe cleaning



Heating

Heaters & Accessories



Measure, test & inspect

Building and wood moisture meters, Distance measuring devices, Inspection devices, Temperature measuring devices



Hand- and special tools

Shears, Pliers & Special tools



POS

POS

Contents

01

02

03

04

05

06

07

80

09



Soldering and brazing


The solder product family has traditionally been the largest in our history.

Alongside soldering and brazing devices, we include pyrography sets, solders, fluxes and accessories in the range.

Soldering is a process for joining metallic materials such as copper and copper alloys, nickel and iron materials.

The difference between soldering and brazing is in the so-called liquidus temperature (the temperature at which the solder is in liquid form).

If this temperature is below 450°C, it is soldering. If the temperature is above 450°C, it is brazing.





Soldering

Brazing

In the area of soldering, we have a range of gas and electro soldering devices. For brazing, we offer only gas soldering devices.

Both versions work only with the aid of a molten nonferrous metal alloy, a solder. It is important that the melting temperature of the solder is always below the melting temperatures of the connected base materials. These are wetted by the liquid solder, but not melted.

Check your choice of solder or ask about our "Lötfibel" or our "Lötnavigator" associated with the respective product labelling.







02

03

04

05

06

07

08



Soldering iron

Proven & reliable

Heating time: approximately 2 minutes | Softgrip plastic handle

Product coverage

- Electronics
- Electrical engineering
- Model construction
- Sheet metal processing
- Tiffany works
- Jumper wires
- Solder lugs
- Row soldering with faster soldering results

15 W

Art.-No. 1500000544 EAN 4004625380727



Delivery

- Plated Cu-tip straight / sharp
- VA heater element pipe with heat shield Ø 4.0 mm
- Connection cable (rubber) 1.5 m
- Equipment support

25 W

Art.-No. 35951 EAN 4004625359518



Delivery

• Plated Cu-tip straight / sharp

- VA heater element pipe with heat shield Ø 4.0 mm
- Connection cable (rubber) 1.5 m
- Equipment support

40 W

Art.-No. 35952 EAN 4004625359525



Delivery

- Nickel-plated copper tips straight / sharp and angled / flat
- VA heater element pipe with heat shield Ø 5.0 mm
- Connection cable (rubber) 1.5 m
- Equipment support

60 W

Art.-No. 35953 EAN 4004625359532



Delivery

- Nickel-plated copper tips straight / sharp and angled / flat
- VA heater element pipe with heat shield Ø 5.8 mm
- Connection cable (rubber) 1.5 m
- Equipment support

80 W

Art.-No. 35954 EAN 4004625359549



Delivery

- Nickel-plated copper tips straight / sharp and angled / flat
- VA heater element pipe with heat shield Ø 7.0 mm
- Connection cable (rubber) 1.5 m
- Equipment support

100 W

Art.-No. 35959 EAN 4004625359594



Delivery

- Nickel-plated copper tips straight / sharp and angled / flat
- ullet VA heating element housing with heat shield Ø 8.0 mm
- Connection cable (rubber) 1.5 m
- Equipment support

09



Soldering iron set

The professional set for soldering

Soldering tip temperature: 300° C | Heating time: approximately 3-5 min | Nominal voltage: 230-240 V

Product coverage

- Soldering of electrical and electronic components and circuit boards, boards, in model construction and radio / communications engineering
- Numerous metallic materials and alloys (mainly brass, copper, iron) are solderable

Product key features

- With retaining clips (third hand)
- Stand secure station with convenient storage
- Soldering accessory compartment

Performance: 30 W

Art.-No. 1500000041 EAN 4004625368596



Delivery

- 1x Soldering iron set
- 2x Soldering tips
- 1x Electronic solder 20 g
- 1x Cleansing sponge



Professional soldering iron set

The perfect set for soldering in a plastic case

Rated voltage: 230 V/50 Hz | Soldering tip temperature: 25 W \rightarrow 420°C, 80 W \rightarrow 550°C | Heating time approximately 2 minutes

Product coverage

- Soldering in electronics, electrical engineering, models & sheet metal processing of thin sheets up to max. 0.8 mm
- Jumper wires up to 2.5 mm
- Connections to about Ø 2 mm
- Larger solder lugs

Product key features

- Includes Equipment storage
- Professional soldering accessories

Performance: 25 & 80 W

Art.-No. 35060 EAN 4004625022634



- 1x Soldering iron 25 W
- 1x Soldering iron 80 W
- 1x Solder grease 20 g
- 1x Braid 2.5 mm x 1.6 m
- 1x Electronic solder 100 g





Electronic soldering station

Ideal for soldering of electronic components

Heating time: approximately 1 min | Nominal voltage: Primary: 230 V \sim /50 Hz; secondary: 12 V for soldering | max. Current consumption: 0.2 A | Soldering tip temperature: approximately 150°C \sim 450°C

Product coverage

- Soldering of printed circuit boards and electronic components
- Intricate soldering works in the field of handicrafts

Product key features

 The electronically monitored controlling of the working temperature enables professional work

Performance: 30 W/12 V

Art.-No. 35960 EAN 4004625359600

Delivery

- 1x Soldering station
- 1x Cleaning sponge
- 1x Piston holder





Brand

The ideal set for the painting and refining of wooden objects and furniture -Professional handling for a creative pastime

Rated voltage: 230-240 V; 50 Hz

Product coverage

- Writing and drawing on wood
- Delicate embellishments of wood surfaces (eg ornaments.)
- Writing & drawing on leather & cork

Product key features

- With the different burn points and branding irons many different patterns can be generated
- În plastic case

Performance: 30 W

Art.-No. 30991 EAN 4004625309919

- Delivery • 1x Alembic / bolt head
- 10x Burn tips
- 9x Branding iron
- 1x Template
- 1x Soldering tip
- 1x Knife insert • 1x Jaws for knife use
- 1x Workstand



01

02

03

04

05

06

07

08

09



RoQuick

The soldering gun promises fast, accurate and reliable soldering

Soldering tip temperature: 510°C | Heating time: approximately 6 seconds | Rated voltage: 230-240 V

Product coverage

- Delicate soldering in model construction, electronics and electrical engineering
- Jumper wires up to 1.5 mm
- Small to medium solder lugs
- Small row soldering with faster soldering results
- Thin sheets up to 0.4 mm

Performance: 100 W

Art.-No. 35957 EAN 4004625359570

Delivery

- 1x Soldering gun
- 2x Cu solder grinder





RoPen 1300

The small, handy gas holder for delicate soldering work

Working temperature: approximately 450°C-600°C

Product coverage

- Delicate soldering work with open flame or catalytic soldering head with soldering tip (eg model construction or craft work.)
- Pyrotechnic works

Product key features

- Refillable
- · Anywhere and quick to deploy

Art.-No. 35115 EAN 4004625015124





Micropen Set 1300

Gas soldering iron with catalyte soldering tip for various soldering works Working temperature: approximately 450°C-600°C

Product coverage

- Delicate solder works
- Crafts
- Pyrographic works
- Model construction
- Styrofoam cutting
- Shrinking
- Plastic welding
- Tiffany works

Product key features

• Refillable

Art.-No. 35120 EAN 4004625010297

Delivery

- 1x Gas soldering iron with plastic tank and flame jet
- 1x Catalytic head
- 1x Needlepoint for delicate solder work
- 1x Chisel and slanted tip for normal electrical work
- 1x Knife for polystyrene cutting





Hot Pen Piezo Set

The professional gas soldering iron set can easily be used in any position, even upside down

Working temperature: approximately 450°C-600°C

Product coverage

- Delicate soldering work
- Crafts
- Pyrotechnik works
- Model construction
- Styrofoam cutting
- Hot air works
- Plastic welding
- Shrinking
- Deforming

Product key features

- Refillable
- Overhead work possible

10 section

Art.-No. 36060 EAN 4004625360606



Delivery

- 1x Gas soldering iron (with catalytic solder attachment including hot air nozzle and heat reflector.)
- 1x High quality plastic case
- 4x Solder attachments
- 1x Styrofoam cutter
- 1x Electronic solder 20 g
- 1x Storage device
- 1x Cleaning sponge



Pocket Torch Piezo

Lighter and soldering torch in a single device – the ideal universal burner for home improvement, crafts, household and camping

Working temperature: approximately 450°C

Product coverage

- Delicate soldering works with concentrated open flame (eg Model construction.)
- Heat source
- Crafts
- Pyrographic works
- Household use as a lighter
- Camping

Product key features

- Refillable (with RoFill refill gas 35840)
- Piezo ignition
- Safety switches

Art.-No. 35130 EAN 4004625010334



01

02

03

04

05

06

07

08

09



RoFix Set 1800

The soldering torch complete set for beginners in a value pack

Working temperature: 650°C | Working time: 2.5 hours

Product coverage

- Soldering of copper pipes up to max. 28 mm
- Heating
- Thawing
- Melting

Product key features

- It has an integrated fine adjustment valve
- Integrated air supply regulation for precise flame adjustment

Art.-No. 35513 EAN 4004625355138

Delivery

- 1x Soldering torch
- 1x Multigas 300
- 3x RoVlies (Cleaning Fleece)
- 1x Fitting solder paste Rosol 3-100 g
- 1x Fittings paste solder 3-100 g





Hot Pack set

The perfect soldering set for beginners

Working temperature: 650°C | Working time: 2.5 hours

Product coverage

- Soldering of copper pipes up to max. 28 mm
- Heating
- Thawing
- Melting

Product key features

- Integrated fine regulating valve
- Integrated air supply regulation for precise flame adjustment

Art.-No. 18078 EAN 4004625180785

Delivery

- 1x Soldering torch
- 2x Multigas 300 cartridges





RoFire Mini 1450

Small, compact and handy soldering cartridge

Working temperature: 650° C | Working time: approximately 1.5 h |

Point burner: 14 mm

Product coverage

- Soldering for model construction
- Welding of round and square bars up to 3 mm thickness, thin-walled tubes up to max. Ø 10 mm

Product key features

- Small
- Handy

Art.-No. 35503 EAN 4004625355039

Delivery

- 1x Minigas cartridge
- 1x Fine adjustment valve
- 1x Combustion tube
- 1x Point burner Ø 14 mm





Guttering soldering set

Ideal for working outdoors in all weathers

Flame temperature: approximately 2000°C | Working temperature: up to 800°C

Product coverage

- Soldered joints of gutters and downpipes made of copper, galvanised steel and titanium zinc sheets up to 1.5 mm thick
- Tinsmith works

Product key features

• The highly wind stable piston burner can also work on the roof when the wind blows and optimises the soldering process

Art.-No. 35498 EAN 4004625354988

Delivery

- 1x Handle with three-way valve and fixed pilot flame
- 1x High performance burner
- 1x Soldering iron holder
- 1x Windshield
- 1x Flat copper bit 250 g
- 1x Hose assembly 2x G 3/8" L 2 m





RoFlame Premium

The high quality soldering torch for various soldering works

Working temperature: 650°C | Gas leading part made from brass

Product coverage

- Soldering
- Thawing
- Repair and service work in sanitary, heating, refrigeration and air conditioning sector
- Grill lighter

Product key features

- Housing made of sturdy plastic
- Safe and easy handling and accurate centering of the cartridge make working with this blowtorch easy

Art.-No. 35930 EAN 4004625359303





RoFlame Premium Piezo

The high quality soldering torch for soldering with piezo ignition Working temperature: 650°C | Gas leading part made from brass

Product coverage

- Soldering
- Thawing
- Repair and service work in plumbing, heating, refrigeration and air conditioning sector
- Grill lighting

Product key features

- Housing made of sturdy plastic
- Safe and easy handling as well accurate centering of the cartridge make working with this blowtorch easy
- Comfortable piezo ignition

Art.-No. 35931 EAN 4004625359310



01

02

03

04

05

06

07

08

09



RoFlame Premium Set

The soldering torch set for immediate and sustainable use
Working temperature: 650°C | Gas leading part made from brass

Product coverage

- Soldering
- Thawing
- Repair and service work in sanitary, heating, refrigeration and air conditioning sector
- Grill lighter

Product key features

- Housing made of sturdy plastic
- Safe and easy handling and accurate centering of the cartridge make working with this blowtorch easy

With 4x C200 Supergas cartridge

Art.-No. 1000000981 EAN 4004625388440



Delivery

- 1x RoFlame Premium solder lamp
- 4x C200 Supergas cartridges



RoFlame Economy Set

The soldering torch set for immediate and sustainable use

Working temperature: 650°C | High quality burner

Product coverage

- Soldering
- Thawing
- Repair and service work in sanitary, heating, refrigeration and air conditioning sector
- Grill lighter

Product key features

- Housing made of sturdy plastic
- Safe and easy handling and accurate centering of the cartridge make working with this blowtorch easy

With 5x C200 Supergas cartridges

Art.-No. 1000000985 EAN 4004625388488



Delivery

- 1x RoFlame Economy solder lamps
- 5x C200 Supergas cartridges

With 4x C200 Supergas cartridge

Art.-No. 1000000982 EAN 4004625388457

eliverv

- 1x RoFlame Economy solder lamp
- 4x C200 Supergas cartridges





RoFire 1800

The proven high-performance soldering instrument for the handyman and professional

Working temperature: 710°C | Burner: 22 mm | Gas leading parts made from brass

Product coverage

- Brazing of copper pipes up to max. Ø 15 mm
- Soldering up to a max. Ø 22 mm
- Heating

Product key features

- Includes Support bracket
- Replaceable burner nozzle

Art.-No. 35501 EAN 4004625355015

Delivery

- 1x RoFire 1800
- 1x Multigas 300 cartridge





RoFire Piezo 1950

The proven high-performance soldering instrument for the handyman and professionals with piezo ignition system

Working temperature: 750°C | Burner: 22 mm | Gas leading parts made from brass

Product coverage

- Brazing of copper pipes up to max. Ø 15 mm
- Soldering up to a max. Ø 28 mm
- Heating

Product key features

- Includes Piezo ignition
- Includes Support bracket
- Replaceable burner nozzle

Art.-No. 35555 EAN 4004625355558

Delivery

- 1x RoFire Piezo 1950
- 1x Multigas 300 cartridge





Power Mapp

The professional high performance soldering instrument for fast and safe working Working temperature: approximately 1250°C

Product coverage

- For soldering of pipes, sheets and moldings
- · For brazing of pipes, sheets and moldings

Product key features

- Piezo ignition system
- Precise flame adjustment
- Constant gas pressure
- Optimal operation at low temperatures (about -20°C)
- Easy change to other fuel gases with connection 7/16" -EU thread (eg Multigas, Maxigas, Minigas)
- Faster and more economical work compared to conventional soldering equipment
- MAPP Gas special gas mixture for very high working temperatures in single gas devices

Art.-No. 030813E EAN 4004625052907

Delivery

- 1x Power Mapp Burner
- 1x MAPP Gas cartridge





Propane soldering set 1800

Hose soldering device for beginners and advanced

Working temperature: 750°C | Burner unit made of brass

Product coverage

- Soldering up to Ø 28 mm
- Brazing up to Ø 22 mm

Product key features

- Easy
- Exactly adjustable

Art.-No. 30801 EAN 4004625308011

Delivery

- 1x Handle with fine control valve
- 1x Bending burner with union nut
- 1x Brazing torch 22 mm
- 1x Hose assembly G 3/8" L/10 x 1 L 1.5 m



01

02

03

04

05

06

07

80

09



Airprop 2000

The high-performance turbo soldering torch is ideal because of its high and constant flame temperature for soldering and brazing

Working temperature: Approximately 800°C | Gas leading part made from brass

Product coverage

- For brazing (up to max. Ø 28 mm) of copper and steel pipes, sheets and fittings
- For soldering (up to max. Ø 54 mm) of copper and steel pipes, sheets and fittings
- Capillary soldering in sanitary and heating installations
- Warming

Product key features

Adjustable via three-way valve with fixed pilot flame

Art.-No. 030950E EAN 4004625309506

Delivery

- 1x Airprop burner
- 1x Hose assembly 2 m on both sides G 3/4" L
- 1x Top ignitor
- 1x Burner tray
- 1x Key





Turbo soldering set 2000

The high-performance turbo-soldering instrument with universal equipment in a complete set

Flame temperature: 2000°C | Working temperature: 800°C | Gas leading parts made out of brass

Product coverage

- For brazing of copper pipes (up to max. Ø 28 mm), Steel pipes, sheets & fittings
- For soldering of copper pipes (up to max. Ø 54 mm), Steel pipes, sheets & fittings
- Capillary gap soldering in plumbing and heating equipment
- Warming

Product key features

• The universal complete equipment is professionally sorted into a case

Art.-No. 30900 EAN 4004625309001

Delivery

- 1x Ergonomic safety handle with fixed pilot Flame – M 14 x 1 / G 3/8" L
- 1x Bending burner with safety cone seal
- 1x DVGW-approved LPG regulator 4 bar, 8 kg/h
- 1x DVGW-approved hose assemblies 2 m
- 1x Turbo torch Ø 28 mm
- 1x Point burner Ø 14 mm
- 1x Soldering torch Ø 22 mm
- 1x Soldering iron 250 g, Forged copper with set-up devices
- 1x Soldering attachment with 2x copper soldering tips
- 1x Safety ignitor
- 1x 50 mm coloured burner attachment
- 1x Burner support, 1x Hexagonal end wrench



Solder

| Solder wire | Product name | Description | ArtNo. | Grams | Ø mm | |
|--|----------------------|---|-----------------|-------|---------|--|
| ~*:caansist | | | 045253, 045253E | 50 | | |
| O o o o o o o o o o o o o o o o o o o o | Fittings Solder 3 | Quality solder to DIN EN ISO 9453 alloy S-Sn97Cu3 | 045256, 045256E | 100 | 3 | |
| | | | 045255, 045255E | 250 | | |
| 280. | | | 045272, 045272E | 50 | | |
| | Standard solder | Universal solder to DIN EN ISO 9453 alloy S-PB60Sn40 | 045271, 045271E | 100 | 2 | |
| | | | 045270, 045270E | 250 | | |
| 280. | | | 045262, 045262E | 50 | | |
| and particular and pa | Radio solder | Quality solder to DIN EN ISO 9453 alloy S-PB60Sn40 | 045261, 045261E | 100 | 2 | |
| | | | 045260, 045260E | 250 | | |
| 260- | | Quality solder to DIN EN ISO 9453 alloy S-Sn60 Pb40 activated without halogens | 045282, 045282E | 50 | | |
| O Internal Control of the Control of | FIECTIONICS | 045281, 045281E | 100 | 1,5 | | |
| | | corrosion | 045280, 045280E | 250 | | |

| Rod solders | Product name | Description | ArtNo. | Electrodes | Ø/lenght mm | |
|-------------|--------------|---|---------|------------|----------------|--|
| | D 1 + 604 | A11.1.11.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1. | 35601 | 5 | 2/222 | |
| M. Mar | Rolot 601 | Nickel silver brazing rods | 35600 | 20 | 2/333 | |
| | Rolot 602 | Brass welding and brazing rods | 35602 | 5 | 2,5/333 | |
| | Rolot 603 | Brass welding and brazing | 35603 | 8 | 1,5/333 | |
| May 1 | KOIOL 603 | rods | 35803 | 8 | 2/500 | |
| | Rolot 604 | Aluminium brazing and welding rods | 35604 | 5 | 3/333 | |
| | | | 35605 | 20 | 1,5/333 | |
| | Rolot 605 | Gas welding rods | 31251 | 10 | 2/500 | |
| WHILL | | | 31252 | 10 | 3/500 | |
| | Rolot 606 | Silver brazing rod 45 % | 35606 | 1 | 1,5/333 | |
| | | | 35607 | 5 | 2/333 | |
| | Rolot 607 | Brazing rods for copper joints | 35707 | 25 | 2/333 | |
| A Charles | | | 35807 | 25 | 2/500 | |
| | Rolot 608 | Soldering rod for | 35608 | 1 | 5/333 | |
| | KOIOL 008 | general installation work | 045263E | 5 (1 kg) | ca.11/400 | |
| | Rolot 609 | Special | 35609 | 2 | 1,5/333 | |
| | KOIOL 609 | silver brazing rods 12 % | 35809 | 4 | 1,5/500 | |
| | Rolot 610 | Special silver colder C 0/ | 35817 | 5 | 2/330 | |
| With | KOIOL 6 IU | Special silver solder 6 % | 35818 | 8 | 2/500 | |

| Ту | ype Application | Contains flux | Recommended additional flux |
|----|---|------------------|--|
| | Heating installations Bo°C Drinking water installations | No | Rosol 3 fittings solder paste: ArtNo. 045225E – 250 g ArtNo. 045226E – 100 g Soldering flux: ArtNo. 045266E – 35 ml ArtNo. 1000000242 – 120 ml |
| | Gutters, general metal work, telecommunications work Zinc, fine soldering Metallic joints Non-ferrous metals not suitable for stainless steel and aluminium | Yes | Soldering grease ArtNo. 035718E – 20 g soldering fluid ArtNo. 035719E – 24 ml |
| | Electronic components: PCBs, cables/conductors/wires | Yes | Soldering grease ArtNo. 035718E – 20 g soldering fluid ArtNo. 035719E – 24 ml |
| | Electronic components: PCBs, cables/conductors/wires | Yes | Soldering grease ArtNo. 035718E – 20 g soldering fluid ArtNo. 035719E – 24 ml |
| ту | ype Application | Contains flux | |
| | Metallic joints Iron, steel, copper, nickel, cast steel and non-ferrous metals | Yes | Welding and brazing powder ArtNo. 035611E – 50 g |
| | Metallic joints Iron, steel, copper, nickel, cast steel and non-ferrous metals | Yes | Welding and brazing powder ArtNo. 035611E – 50 g |
| | Metallic joints Iron, steel, copper, nickel, cast steel and non-ferrous metals | No | Welding and brazing powder ArtNo. 035611E – 50 g |
| | Metallic joints Aluminium brazing | Yes | - |
| | Welding. For mechanical engineering boiler construction, pipe work and vehicle construction St34–St44, St37T–St44T, St35, St35.8 Boiler steel H I–H II | No | - |
| | Pipe installations gutters, general metal work with copper | Yes | - |
| | Pipe installations gutters, general metal work with copper | No | LP 5 brazing paste ArtNo. 035610E – 160 g |
| | Gutter, Genaral metal work | No | Soldering flux ArtNo. 045266E – 35 ml ArtNo. 1000000242 – 120 ml Soldering fluid "Zink" ArtNo. 045264 – 100 ml |
| | Pipe installations, Metallic joints, Iron, steel and cast steel, non-ferrous metals | Yes | - |
| | Gas installations | No | Brazing paste LP10 ATG: ArtNo. 040450 – 65 g |



Fittings paste solder

Rosol 3

Product coverage

· For soldering of heating and drinking water pipes

Product key features

- Economical
- No soldering corrosion
- Barely visible flux residues
- No air inclusions in the solder joint
- Very good tin plating of the material surface
- Application of solder and fluxes in one operation

Contents: 100 q

Art.-No. 045226E EAN 4004625452264



Contents: 250 g

Art.-No. 045225E EAN 4004625452257





Soft solder flux

DIN EN 29454, 1, 3.1.1.C

Product coverage

• For soldering of copper tubes in the cold and hot water installation

Contents: 35 ml

Art.-No. 045266E EAN 4004625452660



Contents: 120 ml

Art.-No. 1000000242 EAN 4004625374795





Soldering fluid

DIN EN 29454, 1, 3.1.1.A

Product coverage

- General soldering of iron, steel, brass, copper, lead and tin
- For Tiffany works

Contents: 24 ml

Art.-No. 035719E EAN 4004625357194





Zinc soldering fluid

DIN EN 29454.1, 3.2.2.A

Product coverage

• Fluxes for soldering titanium zinc, galvanised steel and refined zinc

Contents: 100 ml

Art.-No. 45264 EAN 4004625452646





Flux paste

LP5

DIN EN 1045 - FH 10

Product coverage

- Brazing of ferrous metals
- For gas and water installation with copper pipes
- Used with Rolot 607

Contents: 160 g

Art.-No. 035610E EAN 4004625356104





Hard soldering paste

LP10 ATG

Product coverage

- Gas copper pipes
- Plumbing installations (drinking water, hot and cold water)
- Copper or brass terminals

Contents: 65 g

Art.-No. 40450 EAN 4004625404508





Solder flux

DIN EN 29454, 1, 3.1.1.C

Product coverage

- Soldering of tin, steel, copper and brass
- For tinning of copper wires

Contents: 20 g

Art.-No. 035718E EAN 4004625357187





Welding and brazing powder

HKM

Product coverage

- Brazing of brass, copper, red brass, nickel silver, bronze and iron
- Welding of cast iron

Contents: 50 g

Art.-No. 035611E EAN 4004625356111



01

02

03

04

05

06

07

08

09

Accessories









Suitable for both DIY enthusiasts as well as the professional

Product coverage

Electronic soldering

Product key features

• High-quality basic equipment for electronic soldering needs

Art.-No. 45150 EAN 4004625451502

Delivery

- 1x Salmiak stone
- 1x Braid
- 1x Electronic solder 11 g
- 1x Radio solder 10 g





Soft solder set

The perfect accessory set for soldering works in heating and sanitary applications

Product coverage

• Installation services in the sanitary sector – especially drinking water installation

Art.-No. 45227 EAN 4004625452271

Delivery

- 3x RoVlies cleaning pads
- 1x Flux paste Rosol 3 100 g
- 1x Fitting solder 3–100 g





Tiffany craft set

The perfect accessory set in the Tiffany craft range

Product coverage

Tiffany craft works

Art.-No. 45120 EAN 4004625451205

Delivery

- 1x Salmiak stone
- 1x Solder fluid 24 ml
- 1x Standard solder 20 g
- 1x Tiffany solder 100 g





Brazing rings CU

Copper brazing containing phosphorus

Product coverage

- Pipe connections, copper lines and connections
- Capillary soldering for copper tube installation in sanitary and heating technology

Product key features

- True to size of the inner diameter of the lugged pipes and fittings
- Full soldering of the solder sleeves
- Particularly economical work due to precisely metered amount of solder

Ø 12 mm – 20 pieces

Art.-No. 040512E EAN 4004625047989



Ø 14 mm – 20 pieces

Art.-No. 040514E EAN 4004625047996



Ø 16 mm – 20 pieces

Art.-No. 040516E EAN 4004625048009



Ø 18 mm – 20 pieces

Art.-No. 040518E EAN 4004625048016





RoVlies

5 pieces

Metal-free cleaning fleece for all metals

Product coverage

• Soap-free cleaning of solder joints in copper pipes

Product key features

No corrosion by metallic abrasion

Art.-No. 045267E EAN 4004625452677





Salmiak stone

Gentle and thorough cleaning

Product coverage

• To clean the tip of the soldering iron



Art.-No. 035910E EAN 4004625359105



65 x 45 x 40 mm

Art.-No. 32355 EAN 4004625323557





Hot Pack burner

The power burner for gas cartridges with 7/16" -EU connection

Working temperature: 650°C | Brass burner

Product coverage

- For soldering of copper pipes up to Ø 28 mm
- Also suitable for heating, thawing and melting

Product key features

• With integrated fine adjustment valve and air supply regulation for precise flame adjustment

Art.-No. 520854E EAN 4004625046401



02

01

03

04

05

06

07

08

09



Propane handle

The ergonomic handle for hose soldering devices

Connection: M 14 x 1-G 3/8" L | Gas leading parts made from brass

Product coverage

• For gas soldering equipment with hose connection

Product key features

- Adjustable
- Three-way valve with fixed pilot flame
- Thermally insulated plastic handle

Art.-No. 030910E EAN 4004625309100





Copper soldering iron

Weight: 250 g | Brass gas burner

Product coverage

- Soldered joints of gutters and downpipes made of copper, galvanised steel and titanium zinc sheets up to 1.5 mm thick
- Tinsmith works
- Extension for all soldering equipment with propane handle M 14 x 1, G 3/8" L

Product key features

- Windbreak
- Storage support

Connection: M 14 x 1

Art.-No. 35499 EAN 4004625354995





Gas regulating valve

Product coverage

• To regulate the flow of gas for welding and soldering equipment

Connection: 7/16" EU

Art.-No. 035723E EAN 4004625357231





Easy Soldering Easy Welding Easy Making

ROTHENBERGER INDUSTRIAL

The professional answer for the handyman



Welding Joint welding and cladding with ROTHENBERGER Industrial arc and Gas welding equipment. Our range focuses its equipment range on the needs of the handyman and the professional user. Under the category of arc welding, there are both conventional AC welding transformers for welding rod electrodes as well as modern inverter welding machines, which facilitate their low weight mobile applications.


Our MIG/MAG welding machines for welding different work pieces with wire electrodes under inert gas combines high quality welds in steel, stainless steel and aluminium materials with ease of use. For simple and inexpensive welding, a cored wire welding machine completes our range. A selection of different welding equipment for arc welding is available as required by the user. Sleeve welding units for welding of plastic pipes, such as PP, PB, PE or PVDF, in the installation section complement the ROTHENBERGER Industrial welding range. The devices have different power levels and the equipment is simple and safe to use. Suitable for use on construction sites, they allow the handyman as well as the professional easy and reliable installation of modern plastic pipes during the installation of plumbing and heating systems.



Gas welding







Gas welding torches



Roxy Kit Plus

The Roxy Kit Plus is a universal gas welding and brazing torch for an ambitious handyman and a true professional

The complete set comes with a gas and oxygen tank and is therefore ready to use. In addition to a high performance welding nozzle, the kit includes three micro-nozzles, which allow professional work in areas such as precision mechanics and model construction. The device is TÜV-certified and has all the required safety devices. Gas and oxygen return valves are already integrated.

Product coverage

- General welding work
- Brazing work
- Precision engineering
- Craft
- Model construction
- Optics
- Jewellery making • Goldsmith works
- Bending works
- Extrusions
- Working area: 0.1 mm-2.5 mm Material strength

Product key features

Ready to use

Includes Gas and oxygen bottles

Art.-No. 35740 EAN 4004625357408



Delivery

- 1x Maxigas 400
- 1x Oxygen disposable bottle 110 bar
- 1x Burner key
- 1x Micro nozzle adapter
- 1x Nozzle mixing tube
- 1x Nylon protective goggles A5
- 3x Micro-Nozzles 0.4 mm, 0.5 mm and 0.6 mm
- 1x Gas regulator valve
- 1x Carrying frame
- 1x High performance welding handle
- 1x High performance welding nozzle 0.9 mm
- 1x Security top ignitor
- 1x Oxygen pressure reducing valve with non-return function
- 1x Hose pack (gas and oxygen hose, gas hose with non-return function)
- 1x Assortment kit





09

01

02

03


04

05

06

07







Roxy Mapp

The Roxy Mapp is a universal gas welding and brazing torch of the next generation for an ambitious handyman and a true professional

The complete set comes with a gas and oxygen tank and is therefore ready to use. In addition to two high performance welding nozzles, the kit includes three micro-nozzles, which allow professional work in areas such as precision mechanics and model construction. The device is TÜV-certified and has all the required safety devices. Gas and oxygen return valves are already integrated. The use of MAPP Gas enables high working temperatures for oxyacetylene welding.

Product coverage

- General welding work
- Brazing work
- Precision engineering
- Craft
- Model construction
- Optics
- Jewellery making
- Goldsmith works
- Bending works
- Extrusions
- Working area: 0.1 mm-2.5 mm Material strength

Product key features


- Ready to use
- High working temperatures by using MAPP Gas (ROTHENBERGER special gas mixture)

Includes Gas and oxygen bottles

Art.-No. 35760 EAN 4004625357606

Delivery

- 1x Mapp Gas 750 ml
- 1x Oxygen single use bottle 110 bar
- 1x Burner key
- 1x Micro nozzle adapter
- 1x Nozzle mixing tube
- 1x Nylon protector goggles A5
- 3x Micro-Nozzles 0.4 mm, 0.5 mm and 0.6 mm
- 1x Gas regulator valve
- 1x Carrying structure
- 1x High performance welding handle
- 2x High performance welding nozzle 0.9 mm and 1.2 mm
- 1x Security top ignitor
- 1x Oxygen pressure reducing valve with non-return function
- 1x Hose pack (gas and oxygen hose, gas hose with non-return function)
- 1x Assortment kit







Roxy 400L

The Roxy 400L is a universal gas welding and brazing torch for an ambitious handyman and a true professional

The complete set comes with a gas and oxygen tank and is therefore ready to use. In addition to two high performance welding nozzles, the set includes three micro-nozzles, which allow professional work in areas such as precision mechanics and model construction. The equipment is TÜV-certified and has all the required safety devices. Gas and oxygen return valves are already integrated.

Product coverage

- General welding work
- Precision engineering
- Craft
- Model construction
- Optics
- Jewellery making
- · Goldsmith's work
- Bending work
- Extrusions
- Work area: 0.1 mm-2.5 mm Material strength

Product key features

- Ready to use
- Refillable oxygen cylinder 2 l, 200 bar
- Also suitable for use with MAPP Gas (ROTHENBERGER special gas mixture)

Includes gas and oxygen bottles

Art.-No. 35780 EAN 4004625357804

- 1x Maxigas 400
- 1x Oxygen refillable bottle 2 l, 200 bar
- 1x Burner key

Delivery

- 1x Micro nozzle adapter
- 1x Nozzle mixing tube
- 1x Nylon protection goggles A5
- 3x Micro-Nozzles 0.4 mm, 0.5 mm and 0.7 mm
- 1x Gas regulating valve
- 1x Metal universal backplate
- 1x High performance welding handle
- 2x High performance welding nozzles 1.2 mm and 1.5 mm
- 1x Security top ignitor
- 1x Oxygen pressure reducer with 2 manometers
- 1x Hose pack (gas and oxygen hose with non-return function)
- 1x Assortment kit

05

04

06

07

80

09

10



Roxy Universal

The Roxy Universal is a universal gas welding and brazing device for an ambitious handyman and a true professional

This kit is the basic unit, gas and oxygen tanks are not included. The device is intended for use with both disposable and reusable oxygen containers. As far as fuel gas in concerned, Maxigas as well as Mapp Gas can be used. In addition to three high performance welding nozzles, the kit includes three micro-nozzles that enable professional work in areas such as precision mechanics and model construction. The ergonomic handle with gas fine regulation valve for minimum gas consumption, and the hose package with return valve for oxygen and fuel gas guarantee optimum safety. The equipment is TÜV-certified and has all the required safety devices.

Product coverage

- General welding work
- Brazing
- Precision engineering
- Craft
- Model construction
- Optics
- Jewellery making
- Goldsmith's work
- Bending work
- Extrusions
- Warming
- Work area: 0.1 mm 2.5 mm Material strength

Product key features

- Universally applicable for oxygen disposable and reusable containers
- Universally applicable for ROTHENBERGER Gas cartridges 7/16" -EU connection (Maxigas, Multi Gas & Mapp Gas)


Basic device without gas and oxygen tank

Art.-No. 35050 EAN 4004625014301



Delivery

- 1x Burner key
- 1x Micro nozzle adapter
- 1x Nozzle mixing tube
- 1x Nylon protection goggles A5
- 3x Micro-Nozzles 0.4 mm, 0.5 mm and 0.7 mm
- 1x Gas regulator valve
- 1x Metal universal support frame with different mounting brackets
- 1x High performance welding handle
- 3x High performance welding nozzles 1.2 mm, 1.5 mm and 2.0 mm
- 1x Security top ignitor
- 1x Oxygen pressure reducer with 2 manometers
- 1x Oxygen pressure reducing valve with non-return function for disposable containers
- 1x Hose pack (gas and oxygen hose with non-return function)
- 1x Assortment kit





Three gas system AMS RE17 10/10

Gas welding, cutting and brazing torch for the handyman and professional Universally applicable with mobile equipment trolley | Fully equipped with hose assembly, fittings and steel bottle set (filled) | Ready to use | mobile

Product coverage

- Welding
- Flame cutting
- Brazing
- Car repairs
- Body work
- Plumbing, heating and air conditioning systems
- Metal & ironwork in stationary and mobile use

Product key features

- Ready to use
- Processing of iron, steel, sheet metal, pipes, fittings and nonferrous metals With high performance and low consumption
- Secure attachment of steel cylinders by a retaining bracket
- Alternatively Maxigas or Mapp gas can replace acetylene used

Welding range: 0.5 mm – 9 mm | Cutting: 3.0 mm – 25 mm

Art.-No. 35798 EAN 4004625357989

Delivery

- 1x 10 l Filled acetylene cylinder Property bottle of the buyer TÜV-tested
- 1x 10 | Filled oxygen bottle Property bottle of the buyer TÜV-tested
- 1x Maxigas 400-600 ml
- 1x Single telescopic trolley
- 1x Acetylene pressure reducer with 2 manometers
- 1x Oxygen pressure reducer with 2 manometers
- 1x Gas fine adjustment valve for combustible gas cartridges 7/16" EU (Maxigas Multigas, MAPP Gas)
- 1x Hose adapter for gas cartridges 7/16" EU G 3/8" L
- 1x Twin hose A / S 5 m
- 1x Steel case RE17, mounted
- 1x Welding handle RE17
- 1x 5 Welding torches 0.5 mm-9.0 mm
- 1x Wing lever cutting insert with cutting nozzle 3 mm-25 mm
- 1x Heating nozzle 3 mm-100 mm
- 1x Safety heated ignitor
- 1x Flints
- 1x Burner key
- 1x Nozzle cleaner 10 pcs.



01

02

03

04

05

06

07

08

09



RoWeldo 160

Portable electrode welder – single phase with a fan and thermal protection

Rated voltage: 230 V / 50 Hz | Welding current control range: 55-160 A | Power fuse: 16 A | Open circuit voltage: 48 V | Insulation class: H | Protection class: IP21S | Average operating time about 25 % | Infinite adjustment of the welding current | Weight: ca. 6.2 kg

Product coverage

• For the welding of rod electrodes: 1.5 mm-max. 3.25 mm

Product key features

• With fan and thermal protection

Welding current control range: 55 – 160 A

Art.-No. 36015 EAN 4004625360156

Delivery

- 1x Connection cable 230 V
- 1x Electrode holder, mounted
- 1x Ground terminal, mounted
- 1x Welding shield complete with protective and prescription glass
- 1x Chipping hammer
- 1x Wire brush, welding cables firmly mounted



RoCored Welder 180 Combi

Portable electrode cored wire welding machine

Rated voltage: 230 V / 50 Hz \mid Insulation class: H \mid Protection class: IP215 \mid Weight: ca. 6.2 kg

Product coverage

• For the welding of cored wire

Product key features

- Copper welding nozzle
- Adjustable welding wire feed
- Combi device

Welding current: 180 A

Art.-No. 1500002187 EAN 4004625406069



Delivery

- 1x Cored wire welder with strap
- 1x Ground cable with electrode holder
- 1x Welding screen
- 1x Slag brush with hammer
- 1x Welding gun



RoCored Welder 90

Portable cored wire welding machine without gas protection

Rated voltage: 230 V / 50 Hz | Suitable for 0.6 mm-0.9 mm cored wire

Product coverage

- For the welding of cored wire
- Without addition of protective gas

Product key features

- With connection package consisting of burner unit and ground cable with earthing terminal
- Adjustable welding current in two switching stages (45 A / 90 A)

Welding current control range: 45 – 90 A

Art.-No. 1500000542 EAN 4004625380710

Delivery

- 1x Cored wire welder
- 1x Ground cable
- 1x Ground terminal







RoWin 140

Powerful electrode welding machine with advanced inverter technology
Rated voltage: 230 V / 50 Hz | Suitable for TIG welding | Maximum weldable
electrode: 1.6–3.2 mm | Insulation class: H | Protection class: IP21S | Weight: 5 kg

Product coverage

- For electrode welding
- Assembly

Product key features

Infinitely adjustable

Welding current control range: 20 – 140 A Art.-No. 1500002184 EAN 4004625406038

Delivery

- 1x Electrode welder with strap
- 1x Ground cable with electrode holder
- 1x Welding screen
- 1x Slag brush with hammer





RoWin 80

Powerful electrode welding machine with advanced inverter technology Rated voltage: 230 V / 50 Hz | Maximum weldable electrode 1.6–2.6 mm | Insulation class: H | Protection class: IP21S | Weight: 2.5 kg

Product coverage

- For electrode welding
- Assembly

Product key features

Infinitely adjustable

Welding current control range: 10–80 AArt.-No. 1500002185 EAN 4004625406045

Delivery

- 1x Electrode welder with strap
- 1x Ground cable with electrode holder
- 1x Welding screen
- 1x Slag brush with hammer



02

01

03

04

05

06

07

08

09



RoWin 160 Plus

Powerful electrode welding machine with advanced inverter technology

Rated voltage: 230 V / 50 Hz | Suitable for TIG welding | Maximum weldable electrode: 1.6–4.0 mm | Insulation class: H | Protection class: IP215 | Weight: 4.5 kg

Product coverage

- For electrode welding
- Assembly

Product key features


- Infinitely adjustable
- Digital display
- Suitable for steel, stainless steel, cast iron

Welding current control range: 20-160 A

Art.-No. 1500002186 EAN 4004625406052

Delivery

- 1x Electrode welder with strap
- 1x Ground cable with electrode holder
- 1x Welding screen
- 1x Slag brush with hammer





RoWin 160

Powerful electrode welding machine with advanced inverter technology

Rated voltage: 230 V / 50 Hz | Suitable for TIG welding | Maximum weldable electrode: 1.6–4.0 mm | Insulation class: H | Protection class: IP215 | Weight: 4.5 kg

Product coverage

- For electrode welding
- Assembly

Product key features

- Infinitely adjustable
- Suitable for steel, stainless steel, cast iron

Welding current control range: 20 – 160 A

Art.-No. 1500002189 EAN 4004625406076

Delivery

- 1x Electrode welder with strap
- 1x Ground cable with electrode holder
- 1x Welding screen
- 1x Slag brush with hammer



Plastic Welders'



Socket welder CR-RJQ-40

For simple welding of PP, PB, PE and PVDF plastic pipes and sleeves

Working temperature: $260^{\circ}\text{C} \pm 5\%$ | Rated voltage: 220/230 V | Frequency: 50/60 Hz | Weight: 1.6 kg | Dimensions: $340 \times 122 \times 50 \text{ mm}$

Product coverage

• Welding of PP, PB, PE and PVDF plastic pipes and closures

Product key features

• Thermostatically constant controlled

Performance: 600/650 Watt

Art.-No. 36051 EAN 4004625360514



Delivery

- 4x Nonstick heating mandrels and sleeves (20 mm, 25 mm, 32 mm, 40 mm)
- 1x Solid carrying case made of metal
- 1x Stable table stand
- 1x Retaining bolts
- 1x Allen key
- 1x Nonstick heater
- 1x VDE-checked construction cable H05RN-F 3G 0.7 mm



Socket welder CR-RJQ-63

For simple welding of PP, PB, PE and PVDF plastic pipes and sleeves

Working temperature: 260°C ±5 % | Rated voltage: 220/230 V | Frequency: 50/60 Hz | Weight: 1.68 kg | Dimensions: 370 x 135 x 50 mm

Product coverage

Welding of PP, PB, PE and PVDF plastic pipes and closures

Product key features

- Thermostatically constant controlled
- Temperature setting with digital display

Performance: 800/870 Watt

Art.-No. 36052 EAN 4004625360521



Delivery

- 6x Nonstick heating mandrels and sleeves
 (20 mm, 25 mm, 32 mm, 40 mm, 50 mm, 63 mm)
- 1x Solid carrying case made of metal
- 1x Stable table stand
- 1x Retaining bolts
- 1x Allen key
- 1x Table vice for horizontal and vertical use
- 1x Nonstick heater
- 1x VDE-checked construction cable H07RN-F 1.5 mm



Socket welder CR-ZRJQ-63T

For simple welding of PP, PB, PE and PVDF plastic pipes and sleeves

Working temperature: $200^{\circ}C - 279^{\circ}C \pm 5\%$ | Rated voltage: 220/230 V | Frequency: 50/60 Hz | Weight: 1.8 kg | Dimensions: $370 \times 135 \times 50 \text{ mm}$

Product coverage

• Welding of PP, PB, PE and PVDF plastic pipes and closures

Product key features

- Thermostatically constant controlled
- Temperature setting with digital display

Performance: 800/870 Watt

Art.-No. 36062 EAN 4004625360620



Delivery

- 6x Nonstick heating mandrels and sleeves (20 mm, 25 mm, 32 mm, 40 mm, 50 mm, 83 mm)
- 1x Solid carrying case made of metal
- 1x Stable table stand
- 1x Retaining bolts
- 1x Allen key
- 1x Table vice for horizontal and vertical use
- 1x Nonstick heater
- 1x VDE-checked construction cable H07RN-F 3G 1.5 mm



Socket welder CR-ZRJQ-110T

For simple welding of PP, PB, PE and PVDF plastic pipes and sleeves

Working temperature: $200^{\circ}\text{C} - 279^{\circ}\text{C} \pm 5\%$ | Rated voltage: 220/230 V | Frequency: 50/60 Hz | Weight: 2.0 kg | Dimensions: $380 \times 155 \times 60 \text{ mm}$

Product coverage

• Welding of PP, PB, PE and PVDF plastic pipes and closures

Product key features

- Thermostatically constant controlled
- Temperature setting with digital display

Performance: 1200/1300 Watt

Art.-No. 36063 EAN 4004625360637



Delivery

- 3x Nonstick heating mandrels and sleeves (75 mm, 90 mm, 110 mm)
- 1x Solid carrying case made of metal
- 1x Stable table stand
- 1x Retaining bolts
- 1x Allen key
- 1x Table vice for horizontal and vertical use
- 1x Nonstick heater
- 1x VDE-checked construction cable H07RN-F 3G 1.5 mm

Welding

02

01

03

04

05

06

07

08

09

Electrodes & gas welding wire

| Electrodes | Rutile steel electrodes | Stainless steel electrodes | Aluminium electrodes | NiCu electrodes | ArtNo. | Pieces | Lenghth / Ø mm | |
|--|----------------------------|----------------------------|----------------------|--|--|------------------|-------------------------------|--|
| W.A. | Roweld 708 | | | | 35708 | 10 | 300 / 1.5 | |
| | Roweld 709 | | | | 35709 | 10 | 300 / 2 | |
| | Roweld 709 | | | | 31221 | 80 | 300 / 2 | |
| A Control of the Control | Roweld 709 | | | | 31222 | 195 | 350 / 2 | |
| | Roweld 710 | | | | 35710 | 8 | 350 / 2.5 | |
| | Roweld 710 | | | | 31223 | 50 | 350 / 2.5 | |
| A Company | Roweld 710 | | | | 31224 | 125 | 350 / 2.5 | |
| | Roweld 711 | | | | 35711 | 5 | 350 / 3.25 | |
| A STATE OF THE PARTY OF THE PAR | Roweld 711 | | | | 31226 | 87 | 350 / 3.25 | |
| Maria . | Roweld 711 | | | | 31225 | 35 | 350 / 3.25 | |
| 1 Pro | Roweld 712 | | | | 35704 | 5 | 350 / 4 | |
| Mili | | Roweld V2A | | | 31243 | 10 | 300 / 2 | |
| Phill | | | Roweld AL | | 35702 | 10 | 350 / 2.5 | |
| Iku | | | | Roweld NiCu | 35730 | 10 | 300 / 2.5 | |
| Wive also treates | Copper plated steel | Stainless steel | Aluminiumwelding | Flux-cored welding | | | | |
| Wire electrodes | welding wire | welding wire | wire | wire for unalloyed and low-alloyed steel | ArtNo. | Weight / kg | Ø mm | |
| wire electrodes | welding wire | | wire | | ArtNo. 31231 | Weight / kg | Ø mm | |
| Wire electrodes | welding wire | | wire | | | | | |
| | welding wire | | wire | | 31231 | 1 | 0.6 | |
| | welding wire | | wire | | 31231 31232 | 1 | 0.6 | |
| | welding wire | | wire | | 31231 31232 31233 | 1 1 5 | 0.6 0.8 0.6 | |
| | welding wire | | wire | | 31231 31232 31233 31234 | 1 1 5 | 0.6 0.8 0.6 0.8 | |
| | welding wire | | wire | | 31232 31232 31233 31234 | 1 1 5 5 | 0.6 0.8 0.8 0.8 | |
| | welding wire | welding wire | wire | | 31232 31232 31233 31234 31239 | 1 1 5 5 15 | 0.6 0.8 0.8 0.8 | |
| | welding wire | welding wire | wire | | 31231 31232 31233 31234 31239 31240 | 1 1 5 5 15 15 | 0.6 0.8 0.8 0.8 1 | |

| Current in Amps | Application | Welding positions | Material thickness | Sparking voltage | Tensile strength N/mm ² | Expansion % | 01 |
|--------------------|--|----------------------|-----------------------|---------------------|---------------------------------------|----------------|----|
| 30-50 | Arc welding, assembly or repair of iron and low-alloy steel | | 1–3 mm | 45 V | 440-520 | 24 | |
| | | all | 1.5-4 mm | | | | |
| 40-70 | | | 1.5-4 mm | | | | 02 |
| | | | 1.5-4 mm | | | | |
| | | | 2-6 mm | | | | |
| 60-100 | | | 2-6 mm | | | | 03 |
| | | | 2-6 mm | | | | |
| | | | 3–7 mm | | | | |
| 85-140 | | | 3–7 mm | | | | |
| | | | 3–7 mm | | | | |
| 100-160 | | | 4-10 mm | | | | 04 |
| 50-70 | Arc welding, assembly or repair of stainless steel parts: Chemical and petrochemical applications, marine applications, heat exchangers and installations Arc welding, assembly or repair of aluminium parts: Motor blocks, cylinder heads, canisters, tanks, containers, skips etc. all except vertical downwards > 2 mm 55 V | | - | - | 0. | | |
| 50-80 | | PA, PB, PF | >2 mm | 55 V | - | - | |
| 50-90 | Arc welding parts made of cast iron or cast steel, assembly/repair of motor blocks, machine parts, transmissions, pumps, valves and armatures etc. | PA, PB, PF | >2 mm | | - | - | 05 |
| | | | | | | | |

| | Gas supply | Application | |
|--|---|--|----|
| | | Iron / steel use with a MIG/MAG welder | 06 |
| | CO ₂ and Ar-CO ₂ | | 07 |
| | | | 08 |
| | | Stainless steel use with a MIG/MAG welder | 09 |
| | | Aluminium use with a MIG/MAG welder | |
| | no gas | Iron / Steel use with a MIG/MAG welder | 10 |



Electrode holder

Clamping to the right, left and to the front is possible

Product coverage

Suitable for all rod electrodes

200 A / M 8 | up to 2.4 mm

Art.-No. 530209 EAN 4004625302095



300 A / M 8 | up to 3.2 mm

Art.-No. 530210 EAN 4004625302101





Earth terminal

Zinc plated | For M6 cable connections

150 A / M 6

Art.-No. 530211 EAN 4004625302118



200 A / M 8

Art.-No. 530212 EAN 4004625302125





M8 gas nozzle

Gas nozzle for protective gas burners type 10 with M8 thread

Material: Copper, nickel | Screwable | Thread: M 8

Product coverage

• Supply of protective gas in MIG / MAG welding equipment

Cylindrical (2 pieces)

Art.-No. 530220 EAN 4004625302200



Conical (2 pieces)


Art.-No. 530221 EAN 4004625026748



Cylindrical and Conical set (1 of each)

Art.-No. 530226 EAN 4004625302262







15 plus gas nozzle

Gas nozzle for protective gas burners type 15 with M10 thread

Material: Copper, nickel | For Ø 12 mm shafts | Thread: M 10 | pluggable

Product coverage

• Supply of protective gas in MIG / MAG welding equipment

Cylindrical (2 pieces)

Art.-No. 530222 EAN 4004625026755



Conical (2 pieces)

Art.-No. 530223 EAN 4004625302231



Cylindrical and Conical set (1 of each)

Art.-No. 530227 EAN 4004625302279





Point gas nozzle

Gas nozzle for protective gas burners type 15 with M10 thread

Length: 60 mm | Ø Nozzle: 16 mm | Material: Copper, nickel | For Ø 12 mm shafts | Thread: M 10 | Pluggable

Product coverage

• Supply of protective gas in MIG / MAG welding equipment

Cylindrical (2 pieces)

Art.-No. 530224 EAN 4004625302248





Contact tip

Contact tip for wire electrode

Material: bare electrolytic copper

Product coverage

• For MIG / MAG equipment

Thread: M5 | 0.6 x 18 mm

Art.-No. 530230 EAN 4004625302309



Delivery

• 5x Power nozzles

Thread: M5 | 0.8 x 18 mm

Art.-No. 530231 EAN 4004625302316



Delivery

• 5x Power nozzles

Thread: M6 | 0.6 x 25 mm

Art.-No. 530232 EAN 4004625302323



Delivery

• 5x Power nozzles

Thread: M6 | 0.8 x 25 mm

Art.-No. 530233 EAN 4004625302330



Delivery

• 5x Power nozzles

5x Power nozzles

Thread: M6 | 1.0 x 25 mm

Art.-No. 530234 EAN 4004625302347



Delivery

02

01

03

04

05

06

07

08

09



Micro burner and welding nozzle assortment

Nozzles accessories set for the Roxy series gas welding equipment

Art.-No. 35420 EAN 4004625354209

Delivery

- 3x High performance welding nozzles: 1.2 mm – 1.5 mm – 2.0 mm
- 3x Micro nozzles: 0.4 mm 0.5 mm 0.7 mm





Angle magnet

For the fixing and aligning of flat and round weldments

Fusing range: 30°, 45°, 60°, 75°, 90°

100 x 65 mm

Art.-No. 530213 EAN 4004625302132



120 x 90 mm

Art.-No. 530214 EAN 4004625302149





Wire brush

The perfect cleaner for coarse matters

Product coverage

- Cleaning of castings
- · Cleaning of metal surfaces

Product key features

- Handle made of high quality wood
- Stable metal bristles

3 rows

Art.-No. 561351E EAN 4004625027677



4 rows

Art.-No. 561352E EAN 4004625027684





Flame retardant mat

Continuous temperature resistance 900°C (short term up to 1100°C) | Especially suited for temperatures above 800°C with liquid slag | Melting point in direct flame impingement 840°C

Product coverage

 Provides protection of up to 1000°C of soldering flame and welding heat for ground surfaces (floors, ceilings, walls, wall coverings, cables, carpets and other high fire risk materials)

Product key features

- · Very flexible / Good formability
- Long service life
- High sliding and cut resistance

25 x 25 x 0.4 cm

Art.-No. 031051E EAN 4004625006931







Safety top lighter

The safe gas lighter for all soldering and welding equipment

The fuel gas is ignited safely in the pan by direct action of the spark | Flint replaceable

Product coverage

Safe gas ignition

- Product key features

 Gas/air mixture collects in the pot, so can be fired safely even in windy conditions
- Durable flint

Art.-No. 032093E EAN 4004625320938





Protective gas nozzle cleaner

The perfect complement for the cleaning of protective gas nozzles

Includes 3x Cleaning knives

Art.-No. 530219 EAN 4004625302194



10

01

02

03

04

05

06

07

08



Pressure reducer with 2 manometers

Pressure flow can be adjusted manually with 2 manometers | Contents gauge: 0-315 bar | With shut-off valve and hose connector | W 21.8 x 1, – G 1/4" R

Product coverage

• For protective gas equipment (CO₂, argon and carbon acid)

With 2 manometer

Art.-No. 530217 EAN 4004625302170





Pressure reducer

Single-stage | Up to 130 bar test pressure with safety gauge according to EN 562 | Contents gauge adjustable from 0 to 6 bar | Input: M 10 x 1 right | Output: G 1/4" R with hose nozzle

Product coverage

• For protective gas disposable bottles

With manometer

Art.-No. 530218 EAN 4004625302187





Oxygen pressure reducer

Bottle contents: 110 bar | Input: M 10 x 1 | Output: G 1/4" R

Product coverage

• Fits oxygen disposable bottles with 10 x 1 thread

Product key features

Infinitely adjustable

Includes Flashback valve

Art.-No. 1500000465 EAN 4004625379240





Oxygen pressure reducer

Bottle contents: 200 bar | Working pressure: 0-10 bar | Input: G3/4" R | Output: G1/4" R

Productcoverage

 Suitable for oxygen-returnable bottles: Roxy 400L, Roxy Universal and Standard three gas equipment

Product key features

• Includes Flashback valve

With 2 manometer

Art.-No. 35634 EAN 4004625001240





Hose package Roxy Kit / Roxy Mapp

The hose pack for autogenous welding devices in the Roxy Series

With integrated gas non-return function | Oxygen pressure reducer (integrated non-return function) | Includes Grip with regulating valves (connection: 14×1) | Oxygen hose connection G 1/4" R | Gas hose connection M 10×1

Product coverage

 For autogenous welding equipment from the Roxy Series with oxygen disposable bottles

Hose length: 1.5 m each

Art.-No. 33300 EAN 4004625333006





Hose package Roxy 400L / Roxy Universal

The hose pack for autogenous welding devices in the Roxy Series

With integrated oxygen and gas non-return function | Includes Grip with regulating valves (connection: 14×1) | Oxygen hose connection G 1/4" R | Gas hose connection M 10×1

Product coverage

 For autogenous welding equipment from the Roxy Series with oxygen re-useable bottles

Hose length: 1.5 m each

Art.-No. 33301 EAN 4004625333013





Welding protection goggles

To protect the conjunctiva from burns

Plastic frame with adjustable temples and fold-out side protection | Interchangeable protective glasses | Robust safety glasses with traditional visors | Glass Size: Ø 50 mm

Product coverage

- Brazing and soldering
- Autogenous welding
- Flame cutting

Product key features

• Adjustable length and tilt strap ensures a perfect fit

With DIN 5 Glasses

Art.-No. 035621E EAN 4004625356210





Full protection eyewear

To protect the conjunctiva from burns

Large-scale protection of the eye area due to flexible plastic housing (PVC) | Eyeglass frames made from polyamide | Resizing possible with the adjustable elastic band | Ventilation slots prevent fogging of the safety glasses | Light protection glasses are foldable and interchangeable | Transparent protective glasses | Suitable for people who wear glasses | CE approved according to EN 166/169 | Glass Size: Ø 50 mm

Product coverage

- Brazing and soldering
- Autogenous welding
- Flame cutting

With DIN 5 Glasses

Art.-No. 530207 EAN 4004625302071





Screw ring goggles

To protect the conjunctiva from burns

Stroof glasses with screw cover| Housing made from metal, with elastic band and side air vents | Full protection for the eye area | Interchangeable protective glasses | CE approved according to EN 166/169 | Glass Size: Ø 50 mm | Weight: approximately 80 g

Product coverage

- Brazing and soldering
- Autogenous welding
- Flame cutting

With DIN 5 Glasses

Art.-No. 530208 EAN 4004625302088



02

01

03

04

05

06

07

08

09



RoProtect protective hand shield

Provides protection during welding

Simple housing made from fire-resistant material with handle | Standardised recording of light stabilisers and glass filters

Product coverage

For arc welding process (E, MIG, MAG, TIG)

Glass size: 90 x 110 mm

Art.-No. 530201 EAN 4004625027738





RoProtect protective clear vision shield

For safe and extensive protection during welding

Very sturdy housing made from fire-resistant material, ergonomically shaped | With handle and integrated folding mechanism (foldable light protection glass) | Standardised recording of light stabilisers and glass filters

Product coverage

For arc welding process (E, MIG, MAG, TIG)

Product key features

 Large-scale housing guarantees optimum radiation protection for the eyes and the facial area

Glass size: 90 x 110 mm

Art.-No. 530202 EAN 4004625027745





RoProtect protective head shield

Provides protection during welding

Very sturdy housing made from fire-resistant plastic, ergonomically shaped | Ambidextrous work through the fastening device on the head | Universal fit due to variable sizing | Standardised recording of light stabilisers and glass filters

Product coverage

• For arc welding process (E, MIG, MAG, TIG)

Product key features

 Large-scale housing guarantees optimum radiation protection for the eyes and the facial area

Glass size: 90 x 110 mm

Art.-No. 530203 EAN 4004625027752





Automatic welding protective head shield

The surefire protection during welding – Recommended for DIY and professionals Very solid housing made of fire resistant plastic, ergonomically shaped | Ambidextrous works by fastening device on the head | Infinitely adjustable headband with automatically darkened active welding glass | Passive DIN 4, active DIN 9–13, infinitely adjustable from the outside | Powered by solar cells | Sensitive adjustment | Temperature resistance up to 130°C | Approved according to EN 175 and EN 379

Product coverage

• For arc welding process (E, MIG, MAG, TIG)

Art.-No. 1500000171 EAN 4004625371312





Prescription glass

Replacement glass for ROTHENBERGER Industrial welding protective screens Colourless

Product coverage

• For the protection of welding protection glasses

90 x 110 mm

Art.-No. 530204 EAN 4004625302040

01

02

03

04

05

06

07

80

Delivery

5x Glasses



Protective glass

Replacement glass for ROTHENBERGER Industrial welding protective screens

Product coverage

• Protects conjunctiva against burns

DIN 9 | 90 x 110 mm

Art.-No. 530205 EAN 4004625302057



Delivery

• 2x Glasses

DIN 11 | 90 x 110 mm

Art.-No. 530206 EAN 4004625302064



Delivery

• 2x Glasses



Protective gloves

Quality gloves for optimum heat protection

5-Finger | Size 10 with cuffs | Made from split leather

Product coverage

Protection for the hands during welding

Art.-No. 530216 EAN 4004625302163





Welding protection spray

Silicone and methylene chloride free

Product coverage

- For the cleaning and keeping clean of welding nozzles
- Protection of the material surfaces to be welded
- To protect the pieces to be welded before spraying without impairing the weld

Contents: 400 ml

Art.-No. 40600 EAN 4004625406007





Chipping hammer

Made from metal | With 2 Schagenden (flat / pointed) | Weight: 430 g

Full Metal | Colour: Red

Art.-No. 530215 EAN 4004625302156



09



Industrial gases ROTHENBERGER Industrial is a sought after gas specialist in Europe. All gas cartridges, steel and aluminium bottles are certified and comply with the current standards and guidelines. Safety is very important to us. The hazardous materials as well as hazardous material markings are constantly reviewed and adapted to the legal requirements. Consequently, we guarantee smooth running in terms of transport and storage as well as during use.

Our gases are used in the fields of soldering, welding, in heating and in flame technology. To this end, among other special technical requirements, various connectors and temperature options are to be considered.









C200 Supergas

The C200 Supergas piercing cartridge is universally applicable for devices with a corresponding receiving device

High purity butane gas mixture

Product coverage

- This cartridge may be used with any device category immediate butane pressure according to EN 521
- Blow lamps
- Bunsen burner
- Scout camp stove
- Scout camping lamp

Product key features

• Integrated ILL-security system for leakage limit (according to EN 417: 2012)

- Integrated IEE Seedi

Contents: 190 g / 330 ml

Art.-No. 1500000924 EAN 4004625387269



01

02

03

04

05

06

07

08

Contents: Triple pack: 3x 190 g / 330 ml Art.-No. 1000000984 EAN 4004625388471

Delivery

• 3x C200 Supergas á 190 g





Multigas 300

Tinplate screwable cartridges

Connection: 7/16" EU | Gas mix: 30 % Propane, 70 % Butane



Art.-No. 35510 EAN 4004625355107



Contents: Double pack: 2x 600 ml / 338 g Art.-No. 035510D EAN 4004625014080





Multigas Jumbo

Tinplate screw cartridges – special size

Connection: 7/16" EU | Gas mix: 30 % Propane, 70 % Butane

Product key features

• +25 % more content

Contents: 750 ml / 420 g

Art.-No. 1500000045 EAN 4004625368770



09



Maxigas 400

High performance, welding, cutting and brazing gas

Screw cartridge | Connection: 7/16" EU |

Gas mix: 21.5 % Acetone, 56 % N-Butane Isobutane, 1.5 % Pentane, 21 % Propane

Product coverage

- Gas welding
- Brazing

Product key features

Facilitates high working temperatures

Contents: 600 ml / 352 g

Art.-No. 35570 EAN 4004625355701



Contents: 600 ml / 352 g

Art.-No. 035570-B EAN 4004625054369





Minigas 100

Mini tinplate screwable cartridges

Connection: 7/16" EU | Gas mix: 30 % Propane, 70 % Butane

Contents: 150 ml / 85 g

Art.-No. 35504 EAN 4004625355046





RoFill Super 100

Aluminium gas refill cartridge

Gas mix: 25 % Propane, 75 % Butane

Product key features

- Various nozzle adapter caps
- High purity for the operation of micro soldering torches

Contents: 100 ml / 56 g

Art.-No. 35840 EAN 4004625358405





Topgas 220

Tinplate screwable cartridges

Connection: 7/16" EU | Gas mix: 30 % Propane, 70 % Butane

Product key features

 High stability for the operation of gas appliances in camping, picnics and various laboratory burners

Contents: 370 ml / 220 g

Art.-No. 35201 EAN 4021572075728





Mapp Gas

ROTHENBERGER special gas mixture

Screw cartridge | Connection: 7/16" EU | Gas mix: Butane – Propylene

Product coverage

- Welding
- Brazing

Product key features

- Allows very high working temperatures
- Constant gas pressure at low ambient temperatures

Contents: 750 ml / 411 g

Art.-No. 035551-A EAN 4004625355510





Propane small bottle

Steel gas bottle

Connection: G 3/8" L

Product coverage

Mobile use for roof plumbing and tinsmith works

Product key features

- Suspension facilitates mobile use
- Straightforward and inexpensive refilling with refill spout 032207E
- Lightweight due to lightweight metal bottle

Contents: Empty

Art.-No. 33079 EAN 4004625330791



Delivery

- Propane small bottle with sampling and filling valve (including venting.)
- Feet
- Hook



01

02

03

04

05

06

07

08

09



Helium



Helium

Steel single use bottle

Connection: M 10 x 1 | 100 bar

Product coverage

Balloon Party Set

Contents: 2.2 l

Art.-No. 35206 EAN 4004625352069



Protective gas



Argon

Protective gas steel single use bottle

Connection: M 10 x 1

Product coverage

• To protect the molten bath during MIG welding

Product key features

• 100 % argon

Contents: 950 ml | Full pressure: 60 bar Art.-No. 35775 EAN 4004625357750





Carbon dioxide (CO₂)

Protective gas steel single use bottle

Connection: M 10 x 1

Product coverage

• To protect the molten bath during MAG welding

Contents: 950 ml | Full pressure: 36 bar Art.-No. 35776 EAN 4004625357767



Industrial oxygen





Oxygen (O₂) single use bottle

Steel single use bottle

Connection: M 10 x 1 sx | Not suitable for medical purposes

Product coverage

- Welding in combination with fuel gasBrazing in combination with fuel gas

Contents: 930 ml | Full pressure: 110 bar Art.-No. 35741 EAN 4004625357415





Oxygen (O₂) reusable bottle

Reusable steel bottle

Connection: G 3/4" R | Not suitable for medical purposes | Refillable

Product key features

Refillable

Contents: 2 | Full pressure: 200 bar Art.-No. 35635 EAN 4004625356357





05

04

01

02

03

06

07

80

09



Heating and flaming Flaming devices are used in various areas. The work always proves to be fast and effective.

Among the best known uses of flame technology include the scarfing of roofing felt or bitumen sheeting. However, this is only recommended with warming torches as well as herbicides for an environmentally friendly and economical alternative to conventional weed control.


The installation of roof or bitumen membranes with warming torches has the advantage that no additional adhesive is required and fast work progress is achieved. The bitumen coating is melted by the action of heat with the burner flame and connects with the subsurface.

For the killing of weeds, a special flaming device can used in the garden or on sidewalks. The plants or plant parts are heated briefly with the flame, so that the cell walls burst and the protein molecules are destroyed.

With this action, the entire plant is killed. The optimal time for this is in the Spring. The younger the plant, the better the result.

This treatment must be repeated several times, as the weed can initially grow strongly due to changes in the plant cells.

Other possible applications of flame technology include warmingup, sealing films, tar work, concrete and masonry drying.







Flaming devices



RoMaxi Premium Piezo

The power burner with piezo ignition for flaming and hot glue works

Piezo ignition | Flame temperature: up to 1060°C | Gas pressure: max. 4 bar, 8 kg/h | Short flexing burner with 57 mm | 60 cm long burning pipe, 35° bend

Product coverage

- Scarfing of bitumen sheets
- Warming
- Singe
- Sealing films
- Tar work
- Roof insulation
- Concrete and masonry drying
- Biological weed and moss removal

Product key features

- Lower gas consumption due to exact burner setting
- Piezo ignition

With 5.0 m propane gas hose

Art.-No. 030955E EAN 4004625309551



Delivery

- 1x High performance burner surface finish & edge reinforced with flame stabiliser
- 1x Propane hose 5.0 m, G 2 x 3/8" L
- 1x Handle with three-way valve and fixed pilot flame
- 1x 60 cm burner pipe with burner support



RoMaxi Premium

The power burner for flaming and hot glue works

Flame temperature: up to $1060^{\circ}C$ | Gas pressure: max. 4 bar, 8 kg/h | Flexing burner with 60 cm approx. 35° bend | Burner: Ø 57 mm

Product coverage

- Scarfing of bitumen sheets
- Warming
- Singe
- Sealing films
- Tar work
- Roof insulation
- Concrete and masonry drying

With 5.0 m propane gas hose

• Biological weed and moss removal

Product key features

• Lower gas consumption due to exact burner setting

Art.-No. 030954E EAN 4004625309544

- Delivery
 1x High performance power burner surface finish & edge reinforced with flame stabiliser
- 1x Propane hose 5.0 m, G 2 x 3/8" L
- 1x Handle with three-way valve and fixed pilot flame
- 1x 60 cm burner pipe with burner support

With 5.0 m propane gas hose & propane constant regulator

Art.-No. 030957E EAN 4004625309575



Delivery

- 1x High performance power burner surface finish & edge reinforced with flame stabiliser
- 1x Propane hose 5.0 m, G 2 x 3/8" L
- 1x Propane constant regulator
- 1x Handle with three-way valve and fixed pilot flame
- 1x 60 cm burner pipe with burner support

01

02

03

04

05

06

07

08

09



RoMaxi Economy

The power burner for flaming and hot glue works in an economy version

Flame temperature: up to 1060°C | Gas pressure: max. 4 bar, 8 kg/h | Burner flexing with 60 cm, 35° bend | Burner: Ø 57 mm

Product coverage

- Scarfing of bitumen sheets
- Warming
- Singe
- Sealing films
- Tar work
- Roof insulation
- Concrete and masonry drying
- Biological weed and moss removal

Product key features

· Lower gas consumption due to exact burner setting

With 5.0 m propane gas hose

Art.-No. 030958E EAN 4004625309582



Delivery

- 1x High performance burner galvanised steel & reinforced edges
- 1x Propane hose 5.0 m, G 2 x 3/8" L
- 1x Handle with three-way valve and fixed pilot flame
- 1x 60 cm burner pipe with Burner support

With 5.0 m propane hose & propane constant regulator

Art.-No. 1500000930 EAN 4004625388198



Delivery

- 1x High performance burner galvanised steel & reinforced edges
- 1x Propane hose 5.0 m, G 2 x 3/8" L
- 1x Propane constant regulator
- 1x Handle with three-way valve and fixed pilot flame
- 1x 60 cm burner pipe with burner support



RoMini Premium

The power burner for flaming and hot glue works in a handy small format

Flame temperature: up to 1060° C | Gas pressure: max. 4 bar, 8 kg/h | Short flexing burner with 30 cm, ca. 30° bend | Burner: Ø 54 mm

Product coverage

- Scarfing of bitumen sheets
- Warming
- Singe
- Sealing films
- Tar work
- Roof insulation
- Concrete and masonry drying
- Biological weed and moss removal

Product key features

• Lower gas consumption due to exact burner setting

With 2.0 m propane gas hose

Art.-No. 030961E EAN 4004625309612

Delivery

- 1x High performance burner with flame stabiliser
- 1x Propane hose 2 m, G 2 x 3/8" L
- 1x Handle with three-way valve and fixed pilot flame





Turbo Plus

The broad-beam universal burner with jumbo multi-gas giant for very good flaming results

Flame temperature: 940°C

Product coverage

- Thermal weed and moss eradication
- Warming
- Singe
- Sealing of films

Product key features

- High productivity per unit area
- Wide burner flame
- Piezo ignition
- Eco-Friendly
- Sustainable

With 1x Multigas Jumbo cartridge

Art.-No. 1000001250 EAN 4004625396520

Delivery

- 1x Turbo Plus
- 1x Multigas 300 jumbo cartridge (+25 % more content)



Universal burner

The proven universal burner for various flaming work

Flame temperature: 940°C

Product coverage

- Thermal weed and moss eradication
- Warming
- Singe
- Sealing of films

Product key features

- Piezo ignition
- Eco-Friendly
- Sustainable

Without gas

Art.-No. 30966 EAN 4004625309667

Delivery

• 1x Universal burner

With 1x Multigas 300 jumbo cartridges

Art.-No. 1000000189 EAN 4004625373255



Delivery

- 1x Universal burner
- 2x Multigas 300 Jumbo cartridges

With 2x Multigas 300 cartridges

Art.-No. 1000000557 EAN 4004625380963



Delivery

- 1x Universal burner
- 2x Multigas 300 cartridges



Electric weedkiller

On Page 63 you find the new Electric weedkiller

01

02

03

04

05

06

07

08

09



Propane gas leak protection

Security element for the operation of gas appliances

10-14 kg/h, 2 x G 3/8" L-DVGW checked | Usable together with propane regulators with G 3/8" L outlet | Mounting directly on the controller

Product coverage

- Gas soldering equipment with hose lengths of over 5.0 m
- Required for commercial use

Product key features

• Immediately stops the gas supply in case of hose damage

1.5-4 bar

Art.-No. 035925E EAN 4004625359259





Propane regulator

0.5-4 bar | Infinitely adjustable | W 21.8 x 1/14"L-D max. 8 kg/h | DVGW-checked

Product coverage

 For propane gas bottles 5 kg, 11 kg, 33 kg and gas soldering equipment with hose connection G 3/8" L

0.5-4 bar

Art.-No. 032081E EAN 4004625320815





Propane regulator

0.5-4 bar | Infinitely adjustable | W 21.8 x 1 / 1/14" L-D max. 8 kg/h | DVGW-checked

Product coverage

 For propane gas bottles 5 kg, 11 kg, 33 kg and gas soldering equipment with hose connection G 3/8" L

0.5-6 bar

Art.-No. 032082E EAN 4004625014646





Propane regulator with manometer

0.5-4 bar | W 21.8 x 1/14" L / G 3/8" L-D max. 8 kg/h | DVGW-checked

Product coverage

 For propane gas bottles 5 kg, 11 kg, 33 kg, and gas soldering equipment with hose connection G 3/8" L

Product key features

- High optimal control range for heating torch
- Pressure indication by manometer

Includes Manometer, infinitely adjustable

Art.-No. 032100E EAN 4004625321003





Propane constant regulator

W 21.8 x 1/14" L – G 3/8" L-D max. 8 kg/h | DVGW-checked

Product coverage

 For propane gas bottles 5 kg, 11 kg, 33 kg and gas soldering equipment with hose connection G 3/8" L

4 baı

Art.-No. 030925E EAN 4004625309254







Propane refill connection

Product coverage

- For connection to propane gas bottles 5 kg, 11 kg, 33 kg
- For the filling of propane small bottles (033079)

W 21,8" L / G 3/8" L

Art.-No. 032207E EAN 4004625322079





Propane gas hose line

Pressure: 2 MPa (20 bar) | Ø 5 mm | Connection: 2 x G 3/8" L | certified according EN 1327

Product key features

• Can be used in conjunction with double nipple (item 540255E) as an extension

Length: 2.0 m

Art.-No. 030927E EAN 4004625309278



Length: 2.5 m

Art.-No. 032201E EAN 4004625322017



Length: 5.0 m

Art.-No. 033310E EAN 4004625333105





Double nipple

For the secure lengthening of propane gas hoses

Product coverage

• Extension of propane gas hoses

Connection: 2x G 1/4" L

Art.-No. 540251E EAN 4004625402511



Connection: 2x G 3/8" L

Art.-No. 540255E EAN 4004625001929



04

05

06

07

80

09



Camping, Garden & Household

Whether for the household, camping or a cheerful garden party, ROTHENBERGER Industrial has the right equipment for you.

Our camping stove with either a single flame or two flame option, is simple and safe to handle as well being portable. Whether you are cooking, heating, warming or frying, you always have the optimal solution when travelling. In addition to this, our camping lamp always ensures sufficient illumination.

Our LED lights are excellent for travelling and when stationary have a high luminosity and due to the LED technology, they have a long functional life.

They are light, easy to handle and equipped with additional functions.

With our household items you can make every celebration an unforgettable experience with family or colleagues.

What is a garden party or family celebration without fun helium balloons? With our set every party is a special experience for friends and family.









Crème Brûlée Set

Creative in the kitchen with the professional gourmet burner

Working temperature: 450°C

Product coverage

- The Gourmet Burner is designed for cooking foodstuffs
- Whether used for the flambé, caramelisation, browning, gratinising of food and desserts, the crème brûlée Gourmet Burner makes this easy and secure

Product key features

- Ready to use (including RoFill gas cartridge)
- Easy to use
- Easy refillable
- Big gas tank for long operating time
- Stable
- Piezo ignition

Includes Rofill Gas cartridge

Art.-No. 035126E EAN 4004625053065



Delivery

- 1x Gourmet Burner
- 1x Pedestal
- 1x RoFill Super 100 cartridge



Balloon Party Set

Helium balloons for all ages - Party fun for the whole family

Our balloon Party Set includes everything you need for a great flying balloon ideas. After use, the helium bottle can be disposed of easily. Simply attach balloon, turn the shutter and slowly inflate the balloon to the desired size.

Product coverage

- Ideally suited for occasions such as birthdays
- Wedding
- Carnival
- And many other celebrations

Product key features

- Easy to use
- Ready to use

Art.-No. 035206E EAN 4004625054062

Delivery

- 1x Helium-disposable cartridge 2 l
- 1x Security extraction valve
- 25x Latex balloons á 25 cm
- 1x Egg shaped ball ribbon



Bunsen burner

The ideal burner for heating in goldsmith and laboratory work as well as in glass and plastic processing

Flame temperature: 900° C | Gas consumption in normal use: 45 g/h / 1.0 kW

Product coverage

- Crafts: Optics & Goldsmith's work
- Industrial laboratories Physics, Chemistry and Pharmaceutics
- School lessons: Practical work and experiments

Product key features

- Stable
- Exact flame adjustment

Art.-No. 1500000194 EAN 4004625371503



01

02

03

04

05

06

07

08

09



Scout camping lamp

The mobile light for camping, household and garden

Product key features

- With piezo ignition for easy lighting
- Safe operation
- Quickly ready
- Safe and easy centering
- Quick change of cartridge
- Stable with handle
- Temperature resistant safety glass
- Sturdy plastic housing

Art.-No. 35902 EAN 4004625359020

Delivery

- 1x Camping lamp
- 3x Incandescent mantles





Scout camping cooker

The mobile stove for camping, household and garden

Cooking edition: approximately 14 cm | Operate with piercing Supergas C200 cartridge

Product key features

- Secure stand with handle
- Three-point pot ring non-tilting
- Pot ring, Burner and windshield made from surface treated metal
- Sturdy plastic housing

Art.-No. 35904 EAN 4004625359044





Duo camping cooker

The mobile cooker for camping, household and garden

Power Rating: large burner: 1.70 kW, middle burner: 1.20 kW | Consumption: large burner: 121 g/h, middle burner: 85 g/h | Connect to propane gas bottles (5 kg and 11 kg) with pressure reducer 50 mbar | With hose (0.8 m, Connection: G 1/4" L) and controller (50 mbar)

Product coverage

Recommended for Ø 16-22 cm heads

Product key features

- Two cooking zones with stable pot rings (chrome)
- Enamelled housing
- Wind Stable Burner

Includes Hose and regulator

Art.-No. 35940 EAN 4004625359402



Delivery

- 1x Two-flame stove
- 1x Hose 80 cm with connection 2x G 1/4" L
- 1x Propane regulator 50 mbar



Bench cooker

The ideal companion for camping, outdoor and leisure

Burner made of solid cast iron | Stable construction made of sheet steel

Product coverage

- For stews, soups, stew and mulled wine
- For heating and browning in a pan or wok

Performance: 7.5 kW

Art.-No. 1500001392 EAN 4004625396223

Delivery

- 1x Bench cooker
- 1x Hose assembly 1.5 m G 1/4" L
- 1x Propane constant regulator 50 mbar





Electric weedkiller

Fast environmentally friendly burning or charring of weeds

Rated voltage: 230 V / 50 Hz | 2 metre cable

Product coverage

Weed and moss removal

Performance: 2000 W

Art.-No. 1500002183 EAN 4004625405710

Delivery

- 1x Electric weedkiller (unit disassembles into three parts)
- 1x Nozzle attachment



01

02

03

04

05

06

07

08

09



The mobile light source on the go

With 3 lighting functions for distance and near zones. The elastic lanyard is adjustable in size. The light carrier is adjustable and movable as required.

Product coverage

- Additional lighting while cycling
- Repair work in the dark
- Leisure activities (fishing, camping, hiking)

LED performance: 1 W

Art.-No. 1500001450 EAN 4004625396537



Delivery

- 1x Headlamp
- 3x 1.5 V AAA batteries



LED premium head lamp

The mobile light source on the go

With 3 lighting functions for distance and near zones. The elastic lanyard is adjustable in size. The light carrier is adjustable and movable as required.

Product coverage

- Additional lighting while cycling
- Repair work in the dark
- Leisure activities (fishing, camping, hiking)

LED performance: 3 W

Art.-No. 1500001451 EAN 4004625396551



Delivery

- 1x Headlamp
- 3x 1.5 V AAA batteries



LED multi function light

The handy multifunctional light with USB output

18x powerful white LED | Dimming function 100 % – 50 % | Strong lithium-ion battery | Rechargeable battery | Charging options: 230 V (power outlet), 12 V (car) and 5 V (USB)

Product key features

- USB output for charging of mobile devices
- Easy installation due to hook or magnet

Art.-No. 1500000891 EAN 4004625386804

Delivery

- 1x LED multifunction light
- 1x 230 V charger
- 1x 12 V car adapter
- 1x USB cable





Mini gas lighter

Product key features

- Piezo ignition
- Trigger lock
- Fuel gaugeRefillable

Includes Piezo ignition and gas display

Art.-No. 035992E EAN 4004625359921





Standard gas lighter

Product key features

- Piezo ignition
- Fuel gauge
- Trigger lock
- Refillable
- Child safety lock

Includes Piezo ignition and gas display

Art.-No. 035990E EAN 4004625359907





Storm safe gas lighter

Product key features

- Storm safe
- Piezo ignition
- Fuel gauge
- Trigger lock
- Refillable
- Child safety lock

Includes Piezo ignition and gas display

Art.-No. 035991E EAN 4004625359914





Gooseneck gas lighter

Product key features

- Storm-proof
- Piezoelectric ignition
- Fuel gauge
- Trigger lock
- Refillable
- Child safety
- Portable Gooseneck

Includes Piezo ignition and gas display

Art.-No. 1500000023 EAN 4004625368077





Propane constant regulator

Pressure: 50 mbar | Input: W 21,8 x 1/1 4" L – Output: G 1/4" L | Consumption: 1.5 kg/h

Product coverage

- For heating, boiling and roasting apparatus
- For 5 to 11 kg propane gas bottles

50 mbar

Art.-No. 035921E EAN 4004625359211





Scout replacement glass

Heat-resistant safety glass for camping lamps

Art.-No. 35907 EAN 4004625359075





Incandescent mantle

For gas lamps

Art.-No. 035908E EAN 4004625359082

Delivery

• 3x Mantles





06

05

01

02

03

04

07

80

09



Sanitary installation The pipe processing

and pipe cleaning has a very long tradition at ROTHENBERGER. To this day, an innovative range of products for the plumbing and heating installer sits at the heart of ROTHENBERGER. Many patents, excellent problem solving, robust and high quality tools link the installer with the ROTHENBERGER brand.

ROTHENBERGER Industrial implements this from day one for the handyman. We align our assortment to the needs of the handyman but the professional also benefits.

We put our emphasis on pipe machining and tube cleaning, while the focus is on a simple and secure handling, durability and quality.

In our range you will find the right pliers for each application. Accurately fitting pliers for gentle gripping, high-quality water pump pliers and premium corner pipe wrenches with S-mouth for universal use are available.

Pipe threading, pipe bending, pipe cutters; we offer our customers a large selection of these products in a high quality.

To complete our range, we offer various cleaning equipment for different applications. In this area we place great emphasis on environmentally friendly solutions.







Tube machining



Sanikit

The professional complete set in a plastic case for the handyman

Product coverage

- For all installation work in plumbing and heating systems | Ideal for repair and assembly as well separating steel pipes up to Ø 1 1/4" (31.75 mm)
- Threading to Ø 1" (25.4 mm) | Recommendation: Always use thread cutting oil (eg Ronol Syn 65013)
- Assembly, screw fittings, grommets and sealing of threaded fasteners Up to \emptyset 1 1/4" (31.75 mm)

Art.-No. 070673E EAN 4004625706732

Delivery

- 1x Plastic case
- 1x Ratchet lever, 2-piece
- 1x Ratchet thread cutter Super Cut 1 1/4", with small 8-edge and proven Quick-change
- 3x Thread cutters with small outer-octagon (BSPT right 1/2" 3/4" 1") for tapered (conical) pipe thread 1: 16
- 1x Steel pipe cutter 1 1/4"
- 1x Corner pipe wrench 1"
- 1x Water pump wrench 250 mm, 10"
- 1x Roll of Teflon tape



Tube Cutter 30

Pipe cutters

Robust monobloc sledge and two guide rollers with recess for hemming sewing section

Product coverage

• For cutting copper, brass, aluminium and thin-walled steel pipes

Product key features

• With folding inner de-burrer and spare cutter wheel in the handle

Ø: 3 mm - 30 mm (1/8" - 1 1/8")

Art.-No. 070641E EAN 4004625706411





Tube Cutter 35

Telescopic pipe cutters

Robust construction and two guide rollers with recess for hemming sewing section

Product coverage

• For cutting copper, brass, aluminium and thin-walled steel pipes

Product key features

- With folding inner de-burrer
- Spare cutter wheel in the handle

Ø: 6 mm – 35 mm (1/4" – 1 3/8")

Art.-No. 070941E EAN 4004625709412



01

02

03

04

05

06

07

08

09



Tube Cutter 42

Telescopic pipe cutters

Robust construction and two guide rollers with recess for hemming sewing section

Product coverage

• For cutting copper, brass, aluminium and thin-walled steel pipes

Product key features

- With folding inner de-burrer
- Spare cutter wheel in the handle

Ø: 3 mm-42 mm (1/8"-1 5/8")

Art.-No. 070642E EAN 4004625706428





MiniMax

Pipe cutters

With two support rollers with groove for flanged seam section

Product coverage

• For cutting copper, brass, aluminium and thin-walled steel pipes

Product key features

- Handy design with small working radius
- Effortless tensioning due to large knurled knob
- Ergonomic design of the base body

\emptyset : 3 mm - 28 mm (1/8" - 1 1/8")

Art.-No. 070644E EAN 4004625706442





MiniCut

Pipe cutters

With two support rollers with groove for flanged seam section

Product coverage

• For cutting copper, brass, aluminium and thin-walled steel pipes

Product key features

- Handy design with very small working radius
- Effortless tensioning due to large knurled knob
- Ergonomic design of the base body

Ø: 3 mm - 22 mm (1/8" - 7/8")

Art.-No. 070640E EAN 4004625706404





Steel pipe cutter

Width rollers for reliable guidance and chrome plated spindle | All-steel, drop forged | With chrome plated stem and wide rolls for safe operation

Product coverage

• Ideal for exact cutting of steel pipes

Product key features

- External burr-free cutting pipe threads
- Simple pressure regulation for optimum power transfer to the tube
- Long service life through hardened cutting wheel from high-alloy steel

Ø: 10 mm – 42 mm (1/8" – 1 1/4")

Art.-No. 070643E EAN 4004625706435





Pipe vice

All-steel forged | hinged

Product coverage

• Ideal for pipe working in plumbing and heating installation

Product key features

- With automatic locking hook
- Movable top jaw for secure grip
- Milled upper jaw and lower jaw pad, Hardened and replaceable
- Strong, smooth spindle
- Pipe support
- Epoxy powder coating

Ø: 10 mm - 60 mm (1/8" - 2")

Art.-No. 070674E EAN 4004625706749





SuperCut caliper ratchet

For threading of BSPT right

Ratchet lever 2-piece | Ratchet tap wrench with 8-edge direct support | Safe stop of cutting heads

Product coverage

• For the recording of tapping heads with outer-8-edge

Product key features

- Power saving by lever function
- Handy, lockable switch the in ratcheting direction

Ø: 1/4"-1 1/4"

Art.-No. 070664E EAN 4004625706640





Thread cutting head

For tapered (conical) external pipe thread 1:16 BSPT right | With external 8-edge

Product key features

- Faster cutting through advanced chip ejection chambers
- Reinforced locking ring and precise cutting jaw set
- Cutting jaws interchangeable

Ø External pipe thread: 3/8"

Art.-No. 070755E EAN 4004625707555



Ø External pipe thread: 1/2"

Art.-No. 070756E EAN 4004625707562



Ø External pipe thread: 3/4"

Art.-No. 070757E EAN 4004625707579



Ø External pipe thread: 1"

Art.-No. 070758E EAN 4004625707586



Ø External pipe thread: 1 1/4"

Art.-No. 070759E EAN 4004625707593



02

01

03

04

05

06

07

08

09



SuperCut Set

Professional annular screw set with 3 cutting heads

For threading of BSPT right | Ratchet lever divided (2-piece handle), with 8-socket direct support | Safe Stop of cutting heads | Easy insertion and removal | Faster cutting through advanced chip ejection chambers | Reinforced locking ring and precise cutting back seat | Small teeth and reduced ratchet angle

Product coverage

• For producing precision standardised threaded connections

Product key features

- Power saving by lever function
- Handy, lockable switch the ratcheting direction
- Perfect centering
- Optimised cutting geometry allows easy gating and excellent chip flow
- In plastic carrying case
- Fast cutting through advanced chip ejection chambers
- Easy insertion and removal of the cutter heads

With 3 cutting heads: Ø 1/2" - 3/4" - 1"

Art.-No. 070780X EAN 4004625707807

Delivery

- 1x Thread cutting ratchet
- 1x Cutting head 1/2"
- 1x Cutting head 3/4"
- 1x Cutting head 1"
- 1x Plastic case
- 1x Ratchet lever 2-piece





SuperCut Premium

Annular screw set with 4 cutting heads

For threading of BSPT right | Ratchet lever divided (2-piece handle), with 8-socket direct support | Safe Stop of cutting heads | Easy insertion and removal | Faster cutting through advanced chip ejection chambers | Reinforced locking ring and precise cutting back seat | Small teeth and reduced ratchet angle

Product coverage

For producing precision pipe threaded connections

Product key features

- Power saving by lever function
- Handy, lockable switch the ratcheting direction
- Perfect centering
- Optimised cutting geometry allows easy gating and excellent chip flow
- In plastic carrying case

With 4 cutting heads: Ø 1/2" – 3/4" – 1" – 1 1/4"

Art.-No. 070669E EAN 4004625706695

Delivery

- 1x Plastic case
- 1x Thread cutting ratchet
- 1x Cutting head 1/2"
- 1x Cutting head 3/4"
- 1x Cutting head 1"
- 1x Cutting head 1 1/4"
- 1x Ratchet lever 2-piece





Copper pipe outer brush

For simple and effective treatment of the solder joint

Product key features

• Stable and easy-grip plastic housing

Ø: 12 mm

Art.-No. 854191 EAN 4004625541913



01

02

03

04

05

06

07

08

09

10

Ø: 15 mm



Ø: 18 mm

Art.-No. 854195 EAN 4004625541951



Ø: 22 mm

Art.-No. 854196 EAN 4004625541968





Copper pipe inner brush

For quick cleaning of solder fittings

Ø: 12 mm

Art.-No. 854181 EAN 4004625541814



Ø: 15 mm

Art.-No. 854183 EAN 4004625541838



Ø: 18 mm

Art.-No. 854185 EAN 4004625541852



Ø: 22 mm

Art.-No. 854186 EAN 4004625541869






Internal and external milling cutter

Product coverage

• For effortless deburring of the cut surfaces of copper, aluminium and mild steel pipes

Product key features

 The special arrangement of three ground and hardened steel blade guarantees smooth surfaces without grooves



Art.-No. 011080E EAN 4004625110805





Basin wrench

Chrome vanadium special steel | Drop forged | Very robust

Product coverage

• Ideal for installation of stand taps of washbasins

Product key features

- Optimum power transmission due to-handle
- Swivel claw for clockwise and counterclockwise operation

Ø: 10 mm-32 mm (3/8-1 1/4") | Length: 275 mm

Art.-No. 070676E EAN 4004625706763





Water pump pliers

Chrome vanadium steel | Drop forged | Hardened | Smoothed plier head | Self-clamping jaws | Induction hardened teeth | Crush and pinch protection on the handles | 7 settings

Product coverage

 For secure holding of pipes and flat material, as well as square and hexagonal screw connections

Product key features

 Ideal for hard to reach places due to long, slender plier head – excellent for corners

Ø: 1" / 33 mm | Length: 180 mm / 7"

Art.-No. 070651E EAN 4004625706510



Ø: 1 1/2" / 48 mm | Length 300 mm / 12"

Art.-No. 070652E EAN 4004625706527



Ø: 1 1/4" / 42 mm | Length: 250 mm / 10"

Art.-No. 070650E EAN 4004625706503





45° corner pipe wrench

Chrome vanadium steel | All-steel, drop forged | Hardened, S-shaped mouth | Reinforced sleeve | Smoothed jaws | Secure and non-slip grip by staggered toothing

Product coverage

• For secure holding of pipes, screw fittings, round materials, etc.

Product key features

- · Clamp protection prevents jamming
- Universal use in the installation area

Ø: 1" / 33 mm | Length: 320 mm / 12"

Art.-No. 070656E EAN 4004625706565



Ø: 1 1/2" / 48 mm | Length: 425 mm / 16"

Art.-No. 070657E EAN 4004625706572



Ø: 2" / 60 mm | Length: 560 mm / 20"

Art.-No. 070658E EAN 4004625706589





90° fitting pliers

Chrome vanadium special steel | All-steel, drop-forged

Product coverage

 Plastic jaws ensure safe and gentle grip especially for chrome fittings and polished surfaces, fittings or metal sheets

Product key features

- Non-slip side shape
- Anti-trap prevents jamming
- Jaws made of special plastic

Ø: 1" / 35 mm

Art.-No. 070659E EAN 4004625706596





Plastic pipe cutters

Ideal for plumbers, fitters and mechanics

Product coverage

- For effortless cutting of plastic pipes and multi-layer composite pipes up to Ø 42 mm Product key features
- Adjustable blade base position
- Use a screwdriver to change the blade

Ø: 26-42 mm

Art.-No. 36011 EAN 4004625360118





Plastic pipe cutters

Ideal for plumbers, fitters and mechanics

Product coverage

- \bullet For effortless cutting of plastic pipes and multi-layer composite pipes up to Ø 36 mm Product key features
- Adjustable blade base position
- Use a screwdriver to change the blade

Ø: 36 mm

Art.-No. 36010 EAN 4004625360101





Plastic cutting shears

Ideal for plumbers, fitters and mechanics

Product coverage

- For effortless cutting of plastic pipes and multi-layer composite pipes up to Ø 42 mm diameter
- For effortless one-handed cutting of PE, PP, VPE, PB and PVDF pipes
- For plumbing and heating systems and plant engineering
- Particularly suitable to prepare for socket welding

Product key features

- Fixing the pliers legs for transport
- Automatic & controlled opening of the blade at the push of a button
- Minimum effort during cutting
- Precise force transfer and guided cutter feed
- Point precision without deformation and square cut

Art.-No. 55099 EAN 4004625550991





Economy plastic pipe shears

Ideal for plumbers, fitters and mechanics

Product coverage

- For effortless cutting of plastic pipes and multi-layer composite pipes up to Ø 42 mm Product key features
- With ratchet mechanism for optimal power transfer

Art.-No. 36099 EAN 4004625360996





Premium plastic pipe shears

Ideal for plumbers, fitters and mechanics

Product coverage

- For effortless cutting of plastic pipes and multi-layer composite pipes up to ∅ 42 mm Product key features
- With stainless steel blade and safety latch

Art.-No. 36012 EAN 4004625360125



01

02

03

04

05

06

07

08

09



RoCut plastic pipe shears

Double sided guided blade and ratchet feed | Width pipe support for rectangular section (orbital cut) | Particularly suitable for the preparation for socket welding

Product coverage

 Effortless one-handed cutting of PE, PP PEX, PP and PVDF pipes. For plumbing and heating systems as well as plant engineering



Art.-No. 055090E EAN 4004625006917



Ø: 6-42 mm

Art.-No. 055091E EAN 4004625006894





Replugging ratchet

Reversible R/L | Chrome vanadium steel | With 4-socket set

Product coverage

For universal spud wrenches

Product key features

Quick and easy assembly

Ø: 1/2"

Art.-No. 027180E EAN 4004625006832





Water tap reseating tool

Complete with 2 cutter heads and 2 seals

Cylindrical stepped threaded receptacle for all common fittings

Product coverage

 Uncomplicated application by exact-milling of the valve seat of leaking water valves

Product key features

- Precise work due to adjustable cutting pressure by spring and adjusting screw
- Interchangeable cutters

Ø: 3/8"-1/2"

Art.-No. 070663E EAN 4004625706633



Delivery

- 1x Ground milling machine
- 1x Milling head 3/8"
- 1x Milling head 1/2"
- 2x Seals



Screw hole

For material thicknesses up to max. 4 mm

Product coverage

- For uniform, deformation-free punching of sheet metal, such as steel, V2A, Copper and aluminium
- Ideal for hard to reach places such as in switch cabinets, junction boxes, instrument panels, sink unit basins and bodies

Product key features

- Optimal support due to 3-point gating
- Extremely durable due to metric lag screw

Ø: 32 mm

Art.-No. 021832E EAN 4004625006863



Ø: 35 mm

Art.-No. 021835E EAN 4004625023150





SaniGrip

Syphon pliers

Chrome vanadium special steel | All-steel forged | Chrome plated | Mounted plastic jaws

Product coverage

- Tightening and releasing of plastic pipe threaded connections
- Installation of filtering equipment in swimming pool area with round union nuts up to Ø 62 mm (siphon)

Product key features

- 4-way adjustable joint
- With toothed jaws of plastic

Clamping range: 15-62 mm | Length: 10", 250 mm

Art -No. 070662F FAN 4004625706626



01

02

03

04

05

06

07

08

09



MiniBend

Hand bending device

Product coverage

- Two-hand bending up to 180° of tubes made from soft copper, brass, aluminium and steel
- Refrigeration and air conditioning
- Automotive, hydraulic and pneumatic equipment

Product key features

 Minimum level and bending angle display on Bending scale

Ø: 6 - 8 - 10 mm (1/4" - 5/16" - 3/8")

Art.-No. 025160E EAN 4004625251607





GratFix

The quick trimmer with replaceable HSS universal blade

Product coverage

• For deburring edges on pipes, fittings, holes etc.

Product key features

- Always have a spare blade at hand
- Blade reservoir in the handle

Art.-No. 021659E EAN 4004625216590





Universal spud wrench

Step shape: 3/8" - 1/2" - 3/4" - 1" | Chrome vanadium steel (hardened and nickel-plated) | Square drive 1/2" with cam, hexagonal (6 point) and 12 point synchronisation

Product coverage

 For installation and removal of radiator valve nipples, return screw connections, tap extensions etc.

Product key features

• No canting in nipples and screw connections due to the special design of the step spanner

Art.-No. 073298E EAN 4004625732984





Sliding sleeves kit

Product coverage

- Plastic pipe joints
- Sleeve moulding technology

Product key features

- Fast lot- and thread depth press connections
- Kit packed in a handy plastic case

Art.-No. 1500002197 EAN 4004625406434

Delivery

- 1x Plastic pipe shears 42 mm
- 1x Sliding sleeves device with 3 adapters (12, 16, 20 mm)
- 1x Expandable pliers 12 to 20 mm
- 1x Plastic case



Copper pipe flexible spring

Angled cone, cadmium plated

Product coverage

• For hand bending of soft copper pipe

Ø: 10 mm

Art.-No. 025162E EAN 4004625251621



Ø: 12 mm

Art.-No. 025163E EAN 4004625251638



Ø: 15 mm

Art.-No. 025165E EAN 4004625251652





RoLokus toilet seat assembly wrench

Installation wrench, plastic | Easy installation due to adjustable tilt angle

Product coverage

Mounting of toilet seat sets

Art.-No. 036040E EAN 4004625360408





Mixing nozzle key

Made from robust plastic

Product coverage

• For easy replacement of conventional aerators on taps and fittings

Product key features

• No scratching of chrome-plated surfaces with mixing nozzles and fittings

Art.-No. 070615E EAN 4004625706152





Hemp dispenser

Product coverage

• For thread sealing in heating and plumbing technology

Length: 40 m

Art.-No. 070623E EAN 4004625006979





Teflon band

In practical dispenser

Product coverage

• For clean sealing of metal and plastic screw threads

Length: 12 m

Art.-No. 070624E EAN 4004625706244





SaniFresh

Cleaning spray

Disinfecting and deodorising cleaning spray | Eliminates the risk of disease and allergies | Spray directly on infected surfaces | Eliminates unpleasant odours with a pleasant mint fragrance

Product coverage

- Ideal for air conditioning systems
- Application to eliminate mites, dust, bacteria and fungal spores

Product key features

• Spray can with spray head and spray tube

Contents per bottle: 400 ml

Art.-No. 85800 EAN 4004625858004



01

02

03

04

05

06

07

08



Ronol Syn

High-Performance tapping fluid

Mineral oil free | On synthetic base | Water and sanitation installation allowed | DVGW and SVGW approved

Product coverage

- For perfect and clean threads
- Coolant when sawing metals

Product key features

- Outstanding cooling / lubrication properties
- High pressure resistance
- Long service life of cutting tools
- Skin-friendly
- 100 % water soluble
- Silicone-free and easy to wash out

Contents: 600 ml

Art.-No. 65013 EAN 4004625650134





RoTest leak detection spray

For detecting leakages on gas pipes, gas cylinders, tanks, valves and pipe connections | Neutral towards the common combustible gases and refrigerants | Besides the foaming no further reaction takes place

Product coverage

• Ideal for visual inspection of gas pipelines, pressure vessels, etc.

Product key features

- Simple and cost-effective handling always ready
- Highly sensitive foam spray for fast and safe detection of leaks

Contents: 400 ml / 470 g

Art.-No. 65000 EAN 4004625650004



10

Pipe cleaning



Cleaning spiral with curved tip

Highly flexible cleaning spiral made of spring steel with plastic coating

Ø Spiral: 6.7 mm | With curved tip claw and hand crank

Product coverage

• For the cleaning, clearing and re- making of drainage and sewage pipes made of plastic, cast iron or stoneware with \varnothing 10–50 mm

Product key features

- The plastic coating protects the surface of the pipes and ensures a long service life of the spiral
- No decomposition of the spiral turns
- Easy cleaning

Length: 1.5 m

Art.-No. 072980E EAN 4004625729809



Length: 2.5 m

Art.-No. 072981E EAN 4004625729816



Length: 5.0 m

Art.-No. 072982E EAN 4004625729823





Cleaning spiral with return drill

Highly flexible cleaning spiral made of spring steel

Ø Spiral: 9 mm | With return drill and hand crank

Product coverage

 \bullet Cleaning, clearing and re- making of drainage and sewage pipes made of plastic, cast iron or stoneware with Ø 50–100 mm

Product key features

- Sturdy stainless steel ensures optimum power transfer
- Galvanized version prevents corrosion

Length: 5.0 m

Art.-No. 072984E EAN 4004625729847



Length: 7.0 m

Art.-No. 072985E EAN 4004625729854



Length: 10.0 m

Art.-No. 072986E EAN 4004625729861







Pipe cleaning cables with claw

Highly flexible cleaning spiral made of spring steel

With return drill and hand crank

Product coverage

 Cleaning, clearing and re-making of drainage and sewage pipes made of plastic, cast iron or stoneware with 30–100 mm

Product key features

- Sturdy stainless steel ensures optimum power transfer
- Galvanized version prevents corrosion

Length: 3.0 m | Ø: 6 mm

Art.-No. 1500000139 EAN 4004625370216



01

02

03

04

05

06

07

08

09

Length: 3.0 m | Ø: 9 mm

Art.-No. 1500000140 EAN 4004625370223



Length: 10.0 m | Ø: 9 mm

Art.-No. 1500000141 EAN 4004625370230





Pipe-perfect

Highly flexible cleaning spiral made of spring steel in a plastic spiral holder with Adapter

Adapter allows driving with electric drill and electric screwdriver | Ø Sprial: 6 mm

Product coverage

• Cleaning, clearing and re- making of drainage and sewage pipes made of plastic, cast iron or stoneware with \varnothing 50–100 mm

Product key features

- Sturdy spring steel ensures optimum power transfer
- Galvanised version prevents corrosion
- Closed spiral container made from sturdy plastic
- Compact design
- Adapter for drive with drill and electric screwdriver for comfortable work

Length: 4.5 m

Art.-No. 072990E EAN 4004625053812





RoJet Premium

Drain and syphon cleaner

Product coverage

- Removal of blockages in drains and drain pipes through use of the water pressure Product key features
- The included adapter allows you to connect to almost all commercially available fittings
- Environment-friendly without chemicals
- Low water consumption

Art.-No. 70940 EAN 4004625709405

Delivery

- 1x High pressure cleaning hose 3.0 m with injector nozzle for drains
- 1x High pressure cleaning hose 3.0 m with special cleaning nozzle
- Various adapaters
- Various thicknesses





Compressed air pipe cleaners

Ideal for removing blockages in drains and pipes

Through pressure buildup in the working cylinder via the integrated hand pump and up to 4 bar short term pressure, blockages are forcefully abolished upon relaxation of the pressure pad.

Product coverage

 Clearing and re-making of drainage and sewage pipes (toilets, shower, bath, sinks and washbasins etc.)

Product key features

- Fast, environmentally friendly operation without chemicals
- Easy and safe handling due to pressure safety device
- Sturdy plastic housing
- Universal use through attachments in various sizes and shapes

Art.-No. 1500000006 EAN 4004625367339

04625367339

Delivery

- 1x Compressed air tube cleaner
- 1x Toilet seat attachment (Ø: 20 cm)
- 1x Shower tray drain cover attachment (Ø: 11.3 cm)
- 2x Sink and basin flow attachments (Ø: 6.0 cm/5.0 cm)



RoPump

Suction pressure cleaner

Suction pressure hand pump with ball joint and suction cup | Optimally sealed with triple sealing lip

Product coverage

 Removal of blockages in the siphon and drain region (wash basins, sinks, urinals, showers and baths, etc.)

Product key features

- Easy to use
- Environment-friendly without chemicals
- Sturdy plastic housing
- Easy to clean

Art.-No. 71991 EAN 4004625719916







RoPü

Suction cup to dissolve blockages in the bathroom and kitchen

Maxi: Total length approximately 40 cm | Ø Bell approximately 15 cm Midi: Total length approximately 32 cm | Ø Bell approximately 13 cm Mini: Total length approximately 16 cm | Ø Bell approximately 12 cm

Product coverage

• Removal of blockages in siphon and drain pipes

Product key features

• Fits most toilets and other drains in the bathroom and kitchen (sink, washing up sink, urinals, showers and baths, etc.)

RoPü Maxi

Art.-No. 71920 EAN 4004625719206



RoPü Midi

Art.-No. 1500001739 EAN 4004625400678



RoPü Mini

Art.-No. 1500001444 EAN 4004625396421





Power cleaner

The drain cleaner spray frees stubborn blockages in seconds

With gas pressure clogging by hair, grease, soap residues and other residues can be solved immediately.

Product coverage

 Cleaning, clearing and re-making of siphon and drain pipes (wash basins, sinks, toilets, showers and bathtubs)

Product key features

- Multiple application through 200 ml print cartridge
- Safe Handling
- Without addition of caustic substances
- Reduction of unpleasant odours by fresh lemon scent

Contents: 200 ml

Art.-No. 70631 EAN 4004625706312



01

02

03

04

05

06

07

08

09



Power Cleaner Set

The drain cleaner spray with rubber adapter frees stubborn blockages in seconds With gas pressure clogging by hair, grease, soap residues and other residues can be solved immediately.

Product coverage

 Cleaning, clearing and re-making of siphon and drain pipes (wash basins, sinks, toilets, showers and bathtubs)

Product key features

- Multiple application through 200 ml print cartridge
- Safe Handling
- Universally due to rubber adapter
- Without addition of caustic substances
- Reduction of unpleasant odours by fresh lemon scent

Contents: 200 ml

Art.-No. 70630 EAN 4004625706305

Delivery

- 1x Power Cleaner Drain Spray
- 1x Rubber adapter





Radiator air vent

For optimum venting of radiators

5 mm square | heat-resistant

Product key features

· Quick and clean thanks collecting receptacle

Art.-No. 1500001265 EAN 4004625392911





Heating For rapid heating, for example at construction sites, tents or outdoors, as well as a heat source at outdoor events during the cold season, we have specialised in a mobile, gas-powered heaters range with the appropriate accessories.

Our gas heaters can be operated with standard propane cylinders. The mobile heaters are provided for use with commercially available gas cartridges.

The heaters are characterised by simple and safe handling, they are compact, easy to transport and reliable in use. The optimised design of these devices is aligned with minimum gas consumption.

Our heaters are certified and they comply with currently prescribed standards and guidelines.







Heaters



Eco gas heater

Tower heating units for propane gas bottles

Performance: min. 2.70 kW / max. 4.20 kW | Consumption: 0.2-0.37 kg/h | Suitable for propane gas bottles 5 kg and 11 kg

Product coverage

 For the heating of premises in weatherproof outdoor areas (tents, stalls and well-ventilated room)

Product key features

- Safety ignition
- Robust metal housing with protective grille
- Infinitely adjustable
- Secure connection by forced mounting on standard household gas cylinders
- Thermal fuse

Performance: 2.7-4.2 kW

Art.-No. 35984 EAN 4004625359846



01

02

03

04

05

06

07

80

Delivery

- 1x Gas heater
- 1x Mounting
- 1x Propane hose 0.4 m (both sides G 1/4" L)
- 1x Propane constant regulator 50 mbar



Eco piezo gas heater

Tower heating units for propane gas bottles

Performance: min. 2.70 kW / max. 4.2 kW | Consumption: 0.2–0.37 kg/h | Modell with piezo ignition | Suitable for propane gas bottles 5 kg and 11 kg

Product coverage

 For the heating of premises in weatherproof outdoor areas (tents, stalls and well-ventilated room)

Product key features

- Safety ignition
- Robust metal housing with protective grille
- Infinitely adjustable
- Secure connection by forced mounting on standard household gas cylinders
- Thermal fuse
- Piezo ignition

Performance: 2.7–4.2 kW

Art.-No. 35985 EAN 4004625359853



Delivery

- 1x Gas heater
- 1x Mounting
- 1x Propane hose 0.4 m (both sides G 1/4" L)
- 1x Propane constant regulator 50 mbar

09



RoTurbo 12000

Heat gun with Piezo ignition

Gas category – Gas type: I3B/P – Propane / Butane, I3P – Propane | Rated capacity: I3B/P: 13.3 kW, I3P: 11.9 kW | Gas consumption: 970 g/h | Operating pressure: 300 mbar | Mains voltage: 230 V~/50 Hz | Power Consumption: 39 W | Flame temperature: 930°C | Air emissions: 500 m³/h | Air temperature class: 32 K | Protection type: IPX4 | Motor: IP44 | Protection class: I

Product coverage

 For the heating of premises in weatherproof outdoor areas (tents, stalls and well-ventilated room)

Product key features

- Thermal fuse against overheating
- Double-walled housing made of stainless steel
- Standardised protection grid
- Big strong handle
- Safety ignition
- Constant pressure regulator with hose rupture protection
- Piezo ignition

Performance: 13.3 kW

Art.-No. 1500000050 EAN 4004625368848



Delivery

- 1x Gas heater
- 1x Propane hose 1.0 m (both sides G 1/4" L)
- 1x Propane constant regulator 300 mbar



RoTurbo 19000

Heat gun with Piezo ignition

Gas category – Gas type: I3B/P – Propane / Butane, I3P – Propane | Rated capacity: I3B/P: 18.2 kW, I3P: 16.0 kW | Gas consumption 1325 g/h | Operating pressure: 300 mbar | Mains voltage: 230 V~/50 Hz | Power Consumption: 39 W | Flame temperature: 980°C | Air emissions: 500 m³/h | Air temperature class: 48 K | Protection type: IPX4 | Motor: IP44 | Protection class: I

Product coverage

 For the heating of premises in weatherproof outdoor areas (tents, stalls and well-ventilated room)

Product key features

- Thermal fuse against overheating
- Double-walled housing made of stainless steel
- Standardised protection grid
- Big strong handle
- Safety ignition
- Constant pressure regulator with hose rupture protection
- Piezo ignition

Performance: 18.2 kW

Art.-No. 1500000051 EAN 4004625368855



Delivery

- 1x Gas heater
- \bullet 1x Propane hose 1.0 m (both sides G 1/4" L)
- 1x Propane constant regulator 300 mbar



RoTurbo 35000

Heat gun with Piezo ignition

Gas category – Gas type: I3B/P – Propane / Butane, I3P – Propane | Rated capacity: I3B/P: 34.0 kW, I3P: 29.0 kW | Gas consumption: 2460 g/h | Operating pressure: 1500 mbar | Mains voltage: 230 V~/50 Hz | Power Consumption: 65 W | Flame temperature: 1000°C | Air emissions: 800 m³/h | Air temperature class: 53 K | Protection type: IPX4 | Motor: IP44 | Protection class: I

Product coverage

 For the heating of premises in weatherproof outdoor areas (tents, stalls and well-ventilated room)

Product key features

- Thermal fuse against overheating
- Double-walled housing made of stainless steel
- Standardised protection grid
- Big strong handle
- Safety ignition
- Constant pressure regulator with hose rupture protection
- Piezo ignition

Performance: 34.0 kW

Art.-No. 1500000363 EAN 4004625377062



Delivery

- 1x Gas heater
- 1x Propane hose 1.5 m (both sides G 3/8" L)
- 1x Propane constant regulator 1500 mbar



RoTurbo 35000 SA

Infinitely adjustable heat gun with Piezo ignition

Gas category – Gas type: I3B/P – Propane / Butane, I3P – Propane | Rated capacity: I3B/P: 19.0–34.0 kW, I3P: 17.0–29.0 kW | Gas consumption: 1375–2460 g/h | Operating pressure: 1500 mbar | Mains voltage: 230 V~/50 Hz | Power Consumption: 65 W | Flame temperature: 1000°C | Air emissions: 800 m³/h | Air temperature class: 53 K | Protection type: IPX4 | Motor: IP44 | Protection class: I

Product coverage

 For the heating of premises in weatherproof outdoor areas (tents, stalls and well-ventilated room)

Product key features

- Thermal fuse against overheating
- Double-walled housing made of stainless steel
- Standardised protection grid
- Big strong handle
- Safety ignition
- Constant pressure regulator with hose rupture protection
- Piezo ignition
- Infinitely adjustable

Performance: 34.0 kW | adjustable

Art.-No. 1500000364 EAN 4004625377079



Delivery

- 1x Gas heater
- 1x Propane hose 1.5 m (both sides G 3/8" L)
- 1x Propane constant regulator (1500 mbar) with hose rupture protection

02

01

03

04

05

06

07

08

09



RoTemp M 300

Portable gas heaters for all outdoor activities

For use with multi-gas 300, Multigas Jumbo and Topgas cartridges | Compact design with sturdy base with universal cartridge tray | Infinitely adjustable | High calorific value by heater with reflector

Product coverage

- For camping and other outdoor activities (hunting, fishing, nature observers etc.)

 Product key features
- Economical combustion
- Mobile use
- Alignment of the water jet due to housing with reflector

Performance: 1800 W

Art.-No. 1500001066 EAN 4004625390696





RoTemp M 1000

Portable gas heater with catalyte technology and piezo ignition for all outdoor activities

For use with Multigas 300 Multigas Jumbo cartridge | Compact design with sturdy base and handle

Product coverage

• For camping and other outdoor activities (hunting, fishing, nature observers etc.)

Product key features

- Piezo ignition
- No open flame due to catalyte technology
- Quiet and economical combustion
- Mobile use
- Wind resistant

Performance: 1000 W

Art.-No. 1500000981 EAN 4004625389119





RoTemp M 2000

Portable gas heater with piezo ignition for all outdoor activities

For use with Multigas 300 | Compact, stable design and carrying handle | With cartridge compartment

Product coverage

• For camping and other outdoor activities (hunting, fishing, nature observers etc.)

Product key features

- Piezo ignition
- Low noise combustion
- Mobile use
- Wind resistant
- Stall protection
- Flame sensor / oxygen sensor
- Ceramic heating surface for high performance
- Handle and wall mounting
- Protection grid

Performance: 2000 W

Art.-No. 1500001067 EAN 4004625390702





Low pressure hose line

Pressure: 1 MPa (10 bar) | Ø 5 mm | Connection: 2x G 1/4" L | Certified according to EN 16436-1

Length: 0.4 m

Art.-No. 035914E EAN 4004625359143



Length: 0.8 m

Art.-No. 035915E EAN 4004625359150



Length: 1.5 m

Art.-No. 035916E EAN 4004625359167



Length: 3.0 m

Art.-No. 035917E EAN 4004625359174





03

01

02

04

05

06

07

08

09



Measure, test & inspect The new product

family focuses on specific devices that are used to measure or determine various physical quantities and allow visual inspection of difficult to access objects.

The applications are very versatile. They range from distance measurements, temperature measurements, moisture detector measurements to optical video examination.

All units are of interest to both craftsmen and for the handyman. They are certified, reliable and extremely accurate as a result.







Building and wood moisture meters



Building and wood moisture meter

For fast and accurate moisture measurement of wood materials and building materials

Wood humidity measuring range: $6-44\,\%\pm1\,\%$ | Recommended ambient temperature: 0°C to $+40^{\circ}\text{C}$

Product coverage

- Measuring the residual moisture content of wood-based materials (eg timber.)
- Measuring the residual moisture content of building materials (eg masonry, concrete or screed.)

Product key features

- Results immediately read on the display
- LED for low-light locations
- Easy to use
- Protective cover for probe

Art.-No. 1500000797 EAN 4004625385579

Delivery

- 1x Building and wood moisture meter
- 4x AAA batteries



Distance measuring devices



RO laser meter

Distance meter for the determination of lengths, areas, volumes and distances Integrated Pythagoras additional measurement function for other geometric calculations (for example, diagonals or the height of a facade)

Product coverage

- Calculation of surfaces
- Calculation of volumes
- Calculation of distances
- More geometric calculations using the indirect Pythagoras additional measurement function
- Squaring of buildings

Product key features

- Ease of use
- Measurement accuracy: ± 1.5 mm (± 0.06 in)
- Minimum unit displayed: 1 mm
- Several units: Meter (m), Inch (in), Feet (ft.), Inch + Feet (", ')

Coverage: 35 m

Art.-No. 1500000597 EAN 4004625382639



Delivery

- 1x Distance meter
- 2x LR03 / AAA 1.5 V
- 1x Mini screwdriver
- 1x Nylon pouch
- 1x Hand Strap

Coverage: 50 m

Art.-No. 1500000598 EAN 4004625382653



Delivery

- 1x Distance meter
- 2x LR03 / AAA 1.5 V
- 1x Mini screwdriver
- 1x Nylon pouch
- 1x Hand Strap

03

01

02



06

07

08

09

Inspection devices



Endoscope camera TF 2809

For the exploration of inaccessible places

2.4"-LCD-Screen 480 x 234 Pixel (Colour) \mid Ø Camera head approximately 10 mm \mid Gooseneck length: Approximately 0.90 m \mid Video format: PAL

Product coverage

- Visual inspection of hard to reach places
- Inspection work in the automotive, building trade, industrial equipment, household (example: Chimneys or ventilation pipes)

Product key features

- Video output for further image transmission
- · Flexible, waterproof gooseneck
- Camera head (waterproof) with LED lighting (dimmable)

Includes 2.4 LCD - Gooseneck ca. 0.90 m

Art.-No. 69107 EAN 4004625691076

Delivery

- 1x Endoscope camera
- 1x Double hook attachment
- 1x Hook attachment
- 1x Magnetic attachment
- 1x Mirror attachments
- 1x Video cable
- 4x AA batteries



Endoscope camera TF 3006X

For the exploration of inaccessible places

2.4"-LCD-Screen 480 x 234 Pixel (Colour) | Ø Camera head approximately 10 mm | Gooseneck length: approximately 1.80 m | Video format: PAL

Product coverage

- Visual inspection of hard to reach places
- Inspection work in the automotive, building trade, industrial equipment, household (example: Chimneys or ventilation pipes)

Product key features

- Video output for further image transmission
- Flexible, waterproof gooseneck
- Camera head (waterproof) with LED lighting (dimmable)

Includes 2,4" LCD - Gooseneck ca. 1.80 m

Art.-No. 1500000059 EAN 4004625368923



Delivery

- 1x Endoscope camera
- 1x Waterproof, flexible gooseneck with about 1.80 m in length
- 1x Double hook attachment
- 1x Hook attachment
- 1x Magnetic attachment
- 1x Mirror attachments
- 4x AA batteries
- 1x Plastic case
- 1x USB cable
- 1x Video Connection Cable



Endoscope camera TF 3006SX

For the exploration of inaccessible places

2.4"-LCD-Screen 480 x 234 Pixel (Colour) \mid Ø Camera head approximately 10 mm \mid Gooseneck length: approximately 1.80 m \mid Video format: NTSC / PAL \mid SD-Card-Slot: microSD max. 32 GB \mid Video and photo resolution: 720 x 480 (in colour)

Product coverage

- Visual inspection of hard to reach places
- Inspection work in the automotive, building trade, industrial equipment, household (example: Chimneys or ventilation pipes)

Product key features

- Video output for further image transmission
- Flexible, waterproof gooseneck
- Camera head (waterproof) with LED lighting (dimmable)

Includes 2,4" LCD - Gooseneck ca. 1.80 m

Art.-No. 1500000060 EAN 4004625368930



Delivery

- 1x Endoscope camera
- 1x Waterproof, flexible gooseneck with about 1.80 m in length
- 1x Double hook attachment
- 1x Hook attachment
- 1x Magnetic attachment
- 1x Mirror attachments
- 4x AA batteries
- 1x Plastic case
- 1x USB cable
- 1x Video Connection Cable



Endoscope camera TF3006 BMX

For the exploration of inaccessible places

3,5"-LCD-Screen 320 x 240 Pixel (in colour) \mid Ø Camera head ca. 10 mm \mid Gooseneck length: ca. 1.80 m \mid Video format: NTSC / PAL \mid SD-Card-Slot: microSD max. 32 GB \mid Video and photo resolution: 640 x 480 (in colour)

Product coverage

- Visual inspection of hard to reach places
- Inspection work in the automotive, building trade, industrial equipment, household (example: Chimneys or ventilation pipes)

Product key features

- Video output for further image transmission
- Flexible, waterproof gooseneck
- Camera head (waterproof) with LED lighting (dimmable)

Includes 3.5" LCD - Gooseneck ca. 1.80 m

Art.-No. 1500001391 EAN 4004625396179



Delivery

- 1x Endoscope camera
- 1x Waterproof, flexible gooseneck with about 1.80 m in length
- 1x Double hook attachment
- 1x Hook attachment
- 1x Magnetic attachment
- 1x Mirror attachments
- 4x AA batteries
- 1x Plastic case
- 1x USB cable
- 1x Video Connection Cable

01

02

03

04

05

06

07

08

09



RO Detector

Digital detection device

Maximum detection depth: Ferrous metals \rightarrow 80 mm | Nonferrous metals: 60 mm | Live cables: 50 mm | Wood: 20 mm

Product coverage

- · Locations of ferrous and nonferrous metals
- Locations of conductive lines
- Locations of wooden structures

Product key features

- Minimises the risk of drilling through water or power lines or armouring irons
- Accurate, reliable and easy to use

Art.-No. 1500001135 EAN 4004625390955

Delivery

- 1x Locating device
- 1x Storage bag
- 1x 9 V block battery





Digital multi meter

Simple measurements of various electrical quantities

Ideal for electronics hobbyists and crafters

Product coverage

- Measurement of direct and alternating current voltages
- Measurement of current intensities
- Measurement of resistors

Product key features

- Automatic measuring range detection
- Contactless AC current sensor
- LED work light

Includes LED working light

Art.-No. 1500000806 EAN 4004625385654

Delivery

- 1x Digital Multimeter including LED work light
- 2x AAA batteries



Temperature measuring devices



Economy infrared thermometer

Digital temperature measuring device

Accuracy ±2°C or 2 %

Product coverage

- Non-contact measurement of surface temperature in most organic materials
- Measurement of painted and oxidised surfaces

Measuring range: -30°C up to +380°C

Art.-No. 1500000804 EAN 4004625385630

Delivery

- 1x Economy digital infra red thermometer
- 1x Storage bag
- 1x 9 V Block battery





Professional infrared thermometer

Digital temperature measuring device

Measuring accuracy ±2°C

Product coverage

- Non-contact measurement of surface temperature in most organic materials
- Measurement of painted and oxidised surfaces


Product key features

- Audible alarm in cases of temperature over- and temperature undershoot
- Temperature limits freely adjustable

Measuring range: -50°C-800°C

Art.-No. 1500000805 EAN 4004625385647

- Delivery1x Professional infra red thermometer
- 1x Storage bag1x 9 V Block battery



03

01

02

04

05

06

07

08

09



Hand- and special tools

Shears



Shape cutting shears

Handy, small and agile

Cutting performance: up to 1.8 mm | Stainless steel sheet: up to 1.2 mm

Product coverage

Cutting of sheets

Product key features

- Angled cutting head ensures safe distance from the cut
- Serrated hardened blades for clean, burr-free cuts
- With leverage for optimum power transmission

Left hand cutting

Art.-No. 36161 EAN 4004625361610





Shape cutting shears

Handy, small and agile

Cutting performance: up to 1.8 mm | Stainless steel sheet: up to 1.2 mm

Product coverage

Cutting of sheets

Product key features

- Angled cutting head ensures safe distance from the cut
- Serrated hardened blades for clean, burr-free cuts
- With leverage for optimum power transmission

Right hand cutting

Art.-No. 36162 EAN 4004625361627





Ideal shears

Handy, small and agile

Cutting performance: up to 1.8 mm | Stainless steel sheet: up to 1.2 mm

Product coverage

Cutting of sheets

Product key features

- Angled cutting head ensures safe distance from the interface
- Hardened blades with micro-toothing for clean, burr-free cuts
- With leverage for optimum power transmission

Right and straight cutting

Art.-No. 36163 EAN 4004625361634





Combination pliers

The professional tool with high cutting performance and strong clamping force Maximum leverage by staggered joint axis

Product key features

• With 2-component handle protection

6" - Length: ca. 16 cm

Art.-No. 36121 EAN 4004625361214



01

02

03

05

06

07

08

7" – Length: ca. 18 cm

Art.-No. 36122 EAN 4004625361221



8" - Length: ca. 20 cm

Art.-No. 36123 EAN 4004625361238





Telephone pliers

The professional tool with high cutting performance and strong clamping force Maximum leverage by staggered joint axis | Flat-oval tapered jaw with cutting edges for hard and soft wire

Product key features

• With 2-component handle protection

6" - Length: ca. 16 cm

Art.-No. 36131 EAN 4004625361313



8" - Length: ca. 20 cm

Art.-No. 36132 EAN 4004625361320





Side cutter

The professional tool with high cutting performance and strong clamping force Maximum leverage by staggered joint axis | For hard and soft wire

Product key features

• With 2-component handle protection

6" - Length: ca. 16 cm

Art.-No. 36141 EAN 4004625361412





Wire strippers

The professional tool with high cutting performance and strong clamping force Maximum leverage by staggered joint axis | For hard and soft wire

Product key features

• With 2-component handle protection

6" – Length: ca. 16 cm

Art.-No. 36142 EAN 4004625361429





End cutting pliers

The professional tool with high cutting performance and strong clamping force Maximum leverage by staggered joint axis | Cutting edges induction hardened | CrV-steel

Product key features

Plastic-coated handles

7" – Length: ca. 18 cm

Art.-No. 36143 EAN 4004625361436





Rabitz pliers

The professional tool with high cutting performance and strong clamping force Maximum leverage by staggered joint axis | Cutting edges induction hardened | CrV-steel | Long sides for maximum leverage

Product key features

Plastic-coated handles

10" - Length: ca. 25 cm

Art.-No. 36151 EAN 4004625361511





Rigid foam hand cutter

Fast and easy cutting of rigid foam panels

Power Consumption: 190 W | Nominal voltage: 230 $V\sim/50$ Hz | Heating time: approximately 15 s | Max. Temperature: approximately 315°C | Protection class: IPX0

Product coverage

Accurate and time-saving cutting of polystyrene foam

Product key features

- Fully electronically controlled
- Fast heating time
- Temperature continuously adjustable
- Continuous incision without stopping

Performance: 190 W

Art.-No. 1500000062 EAN 4004625368954



Delivery

- 1x Sturdy plastic case
- 1x Cutter 10 cm
- 1x Cleaning brush
- 1x Tray stand
- 1x VDE cable about 3 m

Optional accessories

Cutting knife – 10 cm

Art.-No. 1500000063 EAN 4004625368961



Cutting knife – 15 cm

Art.-No. 1500000064 EAN 4004625368978



Cutting knife – 20 cm

Art.-No. 1500000065 EAN 4004625368985



Flat cutting knife – 30 cm

Art.-No. 1500000066 EAN 4004625368992



Cutting table - 15 cm

Art.-No. 1500000067 EAN 4004625369005



Groove cutting adapter for pipes

Art.-No. 1500000068 EAN 4004625369012



Cutting knife for pipes up to Ø 20 mm

Art.-No. 1500000069 EAN 4004625369029



Cutting knife for pipes up to Ø 27 mm

Art.-No. 1500000070 EAN 4004625369036



Cutting knife for pipes up to Ø 34 mm

Art.-No. 1500000071 EAN 4004625369043



Cutting knife holder N. 22

Art.-No. 1500000072 EAN 4004625369050



02

01

03

04

05

06

07

08

09







POS

All ROTHENBERGER Industrial individual stocked products are sold in closed transparent packaging. The colour design promotes the attention of customers, the shaped insert contains the product instructions and the transparent packaging support advises on the purchasing decision and helps to promote customer satisfaction.

High quality packaging means that sale walls remain better looking and easy to maintain over a long period of time. The standard size of the packaging makes it very easy to achieve and maintain a wide range of products and replacement of parts.

Making the most of the sales walls with our dealers is the basis of our software-based product line presentation. Distributors and customers benefit from a single, demand-oriented range structure as a supporting element for the consultation and the purchase decision of the customer. With our software-based module design we are shortly going to be able to respond to all the needs of our distributors and to actively support them with an optimised display of ROTHENBERGER Industrial products on sale walls.

Optimally designed, flashy sales displays in colour made from environmentally friendly materials support the supplementary and promotional business of our dealers. The displays can be used universally and can be equipped as needed for multiple applications in the market. Provided with explanatory pictograms, the high quality top signs convey the buying behaviour and have a positive effect on the buying of the products.





Sales wall **Soldering | Welding | Protective gas**



Sales wall **Sanitary**

Alphabetical Index

| 15 plus gas nozzle | 41 | Electric weedkiller 63 | 3 | M | |
|--|----|---|---|--|------|
| 45° corner pipe wrench | | Electrode holder | | M8 gas nozzle | 40 |
| | 72 | Electronic soldering station | 2 | Mapp Gas | 51 |
| | | End cutting pliers | | Maxigas 400 | 50 |
| A | | Endoscope camera TF 2809 90 | 0 | Micro burner and welding | |
| Airprop 2000 | 19 | Endoscope camera TF3006 BMX 91 | 1 | nozzle assortment | 42 |
| Angle magnet | 42 | Endoscope camera TF 3006SX 91 | 1 | Micropen Set 1300 | 14 |
| Arc Welders' | 34 | Endoscope camera TF 3006X 90 | 0 | Mini gas lighter | 64 |
| Argon | 52 | | | MiniBend | 75 |
| Automatic welding protective head shield. 4 | 46 | F | | MiniCut | 68 |
| _ | | Fittings paste solder | 2 | Minigas 100 | 50 |
| В | | Flame retardant mat | 2 | MiniMax | 68 |
| Balloon Party Set 6 | 61 | Flaming devices | 5 | Mixing nozzle key | 76 |
| Basin wrench | 71 | Flux | 2 | Multigas 300 | 49 |
| Bench cooker 6 | 52 | Flux paste | 3 | Multigas Jumbo | 49 |
| Brand | 13 | Fuel gas | | | |
| Brazing rings CU | 25 | Full protection eyewear 45 | 5 | 0 | |
| Brazing torches | 18 | | | Oxygen (O ₂) reusable bottle | 53 |
| Building and wood moisture meter 8 | 39 | G | | Oxygen (O ₂) single use bottle | 53 |
| Bunsen burner 6 | 61 | Gas regulating valve | | Oxygen pressure reducer | 44 |
| | | Gas welding torches | | _ | |
| C | | Gooseneck gas lighter 64 | 4 | P | |
| 1 3 | 49 | GratFix | 5 | Pipe cleaning | . 78 |
| 2, | 52 | Guttering soldering set | | Pipe cleaning cables with claw. | |
| | 47 | | | Pipe-perfect | |
| Cleaning spiral with curved tip | 78 | Н | | Pipe vice | 69 |
| 3 | 78 | Hard soldering paste | | Plastic cutting shears | |
| | 95 | Heaters | | Plastic pipe cutters | |
| | 30 | Helium | | Plastic Welders' | |
| Contact tip | 41 | Hemp dispenser | | Pliers | |
| Copper pipe flexible spring. | | Hose package Roxy 400L / Roxy Universal. 45 | | Pocket Torch Piezo | |
| Copper pipe inner brush | 71 | Hose package Roxy Kit / Roxy Mapp 44 | | Point gas nozzle | |
| The Literature of the control of the | 71 | Hot Pack burner | | Power cleaner | |
| 3 | 26 | Hot Pack set | | Power Cleaner Set | |
| Crème Brûlée Set 6 | 61 | Hot Pen Piezo Set | | Power Mapp | |
| D | | • | | Premium plastic pipe shears | |
| D | | 1 | | Prescription glass | |
| Devices | | Ideal shears | | Pressure reducer | 44 |
| - · 3 ··································· | 92 | Incandescent mantle 65 | | Pressure reducer | |
| Distance measuring devices | | Industrial oxygen | | with 2 manometers | |
| | 59 | Inspection devices | | Professional infrared thermometer | |
| Duo camping cooker 6 | 52 | Internal and external milling cutter 71 | | Professional soldering iron set | |
| E | | 1 | | Propane constant regulator 58, | |
| E | 40 | L . | | Propane gas hose line | |
| | | LED economy head lamp | | Propane gas leak protection | |
| 3 | 33 | LED multi function light | | Propane handle | |
| | 33 | LED premium head lamp 63 | | Propane refill connection. | |
| · · · · · · · · · · · · · · · · · · · | | Lighters | | Propane regulator | |
| Economy plastic pipe shears | 73 | Low pressure hose line 87 | 7 | Propane regulator with manometer | 58 |

| Propane small bottle | 51 | RoVlies | 25 | Thread cutting head | 69 |
|--|-----|-------------------------------|-----|---------------------------------|------|
| Propane soldering set 1800 | 19 | RoWeldo 160 | 34 | Three gas system AMS RE17 10/10 | 33 |
| Protective gas nozzle cleaner | 43 | RoWin 80 | 35 | Tiffany craft set | 24 |
| Protective gas | .52 | RoWin 140 | 35 | Topgas 220 | 50 |
| Protective glass | 47 | RoWin 160 | 36 | Tube Cutter 30 | 67 |
| Protective gloves | 47 | RoWin 160 Plus | 36 | Tube Cutter 35 | 67 |
| | | Roxy 400L | 31 | Tube Cutter 42 | 68 |
| R | | Roxy Kit Plus | 29 | Tube machining | . 67 |
| Rabitz pliers | 96 | Roxy Mapp | 30 | Turbo Plus | 57 |
| Radiator air vent | 81 | Roxy Universal | 32 | Turbo soldering set 2000 | 19 |
| Radio electronic set | 24 | | | | |
| Replugging ratchet | 74 | S | | U | |
| Rigid foam hand cutter | 97 | Safety top lighter | 43 | Universal burner | 57 |
| RO Detector | 92 | Salmiak stone | 25 | Universal spud wrench | 75 |
| RO laser meter | 89 | SaniFresh | 77 | | |
| RoCored Welder 90 | 34 | SaniGrip | 75 | W | |
| RoCored Welder 180 Combi | 34 | Sanikit | 67 | Water pump pliers | 72 |
| RoCut plastic pipe shears | 74 | Scout camping cooker | 62 | Water tap reseating tool | 74 |
| RoFill Super 100 | 50 | Scout camping lamp | 62 | Welding and brazing powder | 23 |
| RoFire 1800 | 18 | Scout replacement glass | 65 | Welding protection goggles | 45 |
| RoFire Mini 1450 | 16 | Screw hole | 74 | Welding protection spray | 47 |
| RoFire Piezo 1950 | 18 | Screw ring goggles | 45 | Wire brush | 42 |
| RoFix Set 1800 | 15 | Shape cutting shears | | Wire strippers | 96 |
| RoFlame Economy Set | 17 | Shears | | | |
| RoFlame Premium | | Side cutter | | Z | |
| RoFlame Premium Piezo | 17 | Sliding sleeves kit | | Zinc soldering fluid | 22 |
| RoFlame Premium Set | 17 | Socket welder CR-RJQ-40 | | J | |
| RoJet Premium | | Socket welder CR-RJQ-63 | | | |
| RoLokus toilet seat assembly wrench | 76 | Socket welder CR-ZRJQ-63T | | | |
| RoMaxi Economy | | Socket welder CR-ZRJQ-110T. | | | |
| RoMaxi Premium | | Soft solder flux | | | |
| RoMaxi Premium Piezo | 55 | Soft solder set | 24 | | |
| RoMini Premium | 56 | Solder flux | 23 | | |
| Ronol Syn. | | Soldering fluid | | | |
| RoPen 1300 | | Soldering iron | | | |
| RoProtect protective clear vision shield | 46 | Soldering iron set | | | |
| RoProtect protective hand shield | 46 | Soldering torches | | | |
| RoProtect protective head shield | 46 | Special tools | | | |
| RoPü | | Standard gas lighter | | | |
| RoPump | | Steel pipe cutter | | | |
| RoQuick | | Storm safe gas lighter | | | |
| RoTemp M 300 | | SuperCut caliper ratchet | | | |
| RoTemp M 1000 | | SuperCut Premium | | | |
| RoTemp M 2000 | | SuperCut Set | | | |
| RoTest leak detection spray | | | . 0 | | |
| RoTurbo 12000 | | Т | | | |
| RoTurbo 19000 | | Teflon band | 76 | | |
| RoTurbo 35000 | | Telephone pliers | 95 | | |
| RoTurbo 35000 SA | | Temperature measuring devices | | | |
| | | | | | |

Numerical Index

| 0 | 035992E | 0707575 | 35201 50 |
|-----------------|--------------------|------------|----------|
| 011080E 71 | 036040E | 070757E | 35206 |
| 021659E | | | |
| | 040512E | 070759E 69 | |
| 021832E | 040514E | 070780X 70 | 35498 |
| 021835E | 040516E 25 | 070941E 67 | 35499 26 |
| 025160E | 040518E 25 | 072980E 78 | 35501 |
| 025162E 76 | 045225E 22 | 072981E 78 | 35503 |
| 025163E 76 | 045226E 22 | 072982E 78 | 35504 50 |
| 025165E 76 | 045253, 045253E 20 | 072984E 78 | 35510 49 |
| 027180E 74 | 045255, 045255E 20 | 072985E 78 | 35513 |
| 030813E | 045256, 045256E 20 | 072986E 78 | 35555 |
| 030910E 26 | 045260, 045260E 20 | 072990E 79 | 35570 50 |
| 030925E 58 | 045261, 045261E 20 | 073298E | 35600 20 |
| 030927E 59 | 045262, 045262E 20 | | 35601 20 |
| 030950E 19 | 045263E 20 | 1 | 35602 20 |
| 030954E | 045266E | 18078 | 35603 20 |
| 030955E 55 | 045267E 25 | | 35604 20 |
| 030957E 55 | 045270, 045270E 20 | 3 | 35605 20 |
| 030958E | 045271, 045271E 20 | 30801 | 35606 |
| 030961E 56 | 045272, 045272E 20 | 30900 | 35607 |
| 031051E | 045280, 045280E 20 | 30966 | 35608 |
| 032081E 58 | 045281, 045281E 20 | 30991 | 35609 |
| 032082E 58 | 045282, 045282E 20 | 31221 | 35634 |
| 032093E | 055090E | 31222 | 35635 |
| 032100E 58 | 055091E | 31223 | 35702 |
| | | | |
| 032201E 59 | 070615E | 31224 | 35704 |
| 032207E 59 | 070623E | 31225 | 35707 |
| 033310E 59 | 070624E | 31226 | 35708 |
| 035126E 61 | 070640E | 31231 | 35709 |
| 035206E 61 | 070641E 67 | 31232 | 35710 |
| 035510D 49 | 070642E 68 | 31233 | 35711 |
| 035551-A 51 | 070643E 68 | 31234 | 35730 |
| 035570-B 50 | 070644E 68 | 31235 | 35740 29 |
| 035610E 23 | 070650E 72 | 31236 | 35741 53 |
| 035611E 23 | 070651E 72 | 31239 38 | 35760 |
| 035621E 45 | 070652E 72 | 31240 | 35775 |
| 035718E 23 | 070656E | 31243 | 35776 |
| 035719E 22 | 070657E 72 | 31244 | 35780 |
| 035723E 26 | 070658E | 31251 20 | 35798 |
| 035908E 65 | 070659E | 31252 20 | 35803 20 |
| 035910E 25 | 070662E | 32355 25 | 35807 20 |
| 035914E 87 | 070663E 74 | 33079 51 | 35809 20 |
| 035915E 87 | 070664E 69 | 33300 44 | 35817 20 |
| 035916E 87 | 070669E 70 | 33301 45 | 35818 20 |
| 035917E 87 | 070673E 67 | 35050 | 35840 50 |
| 035921E 65 | 070674E 69 | 35060 | 35902 62 |
| 035925E 58 | 070676E | 35115 | 35904 62 |
| 035990E 64 | 070755E 69 | 35120 | 35907 65 |
| 035991E 64 | 070756E 69 | 35130 | 35930 |
| · · · · · · · · | | | |

| 25024 | 530006 | 254424 | 450000004 |
|-----------|-----------|---------------|---------------|
| 35931 | 530206 | 854191 | 1500000804 92 |
| 35940 | 530207 | 854193 | 1500000805 93 |
| 35951 | 530208 | 854195 | 1500000806 92 |
| 35952 | 530209 | 854196 | 1500000891 63 |
| 35953 | 530210 40 | 85800 | 1500000924 49 |
| 35954 | 530211 40 | 1000 | 1500000930 56 |
| 35957 | 530212 40 | 1000 | 1500000981 |
| 35959 | 530213 42 | 1000000189 57 | 1500001066 |
| 35960 | 530214 42 | 1000000242 22 | 1500001067 86 |
| 35984 | 530215 47 | 1000000557 57 | 1500001135 92 |
| 35985 | 530216 47 | 1000000981 | 1500001265 81 |
| 36010 73 | 530217 44 | 1000000982 | 1500001391 91 |
| 36011 73 | 530218 44 | 1000000984 49 | 1500001392 62 |
| 36012 73 | 530219 43 | 1000000985 | 1500001444 80 |
| 36015 | 530220 40 | 1000001250 57 | 1500001450 63 |
| 36051 | 530221 40 | | 1500001451 63 |
| 36052 | 530222 41 | 1500 | 1500001739 80 |
| 36060 | 530223 41 | 1500000006 80 | 1500002183 63 |
| 36062 | 530224 41 | 1500000023 64 | 1500002184 |
| 36063 | 530226 40 | 1500000041 | 1500002185 |
| 36099 73 | 530227 41 | 1500000045 49 | 1500002186 |
| 36121 95 | 530230 41 | 1500000050 84 | 1500002187 |
| 36122 95 | 530231 41 | 1500000051 84 | 1500002189 |
| 36123 95 | 530232 41 | 1500000059 90 | 1500002197 |
| 36131 95 | 530233 41 | 1500000060 91 | |
| 36132 95 | 530234 41 | 1500000062 97 | |
| 36141 | 540251E | 1500000063 97 | |
| 36142 | 540255F | 1500000064 | |
| 36143 96 | 55099 | 1500000065 | |
| 36151 | 561351E | 1500000066 | |
| 36161 | 561352E | 1500000067 | |
| 36162 94 | 3013322 | 1500000068 97 | |
| 36163 | 6 | 1500000069 97 | |
| 30103 | 65000 | 1500000070 | |
| 4 | 65013 | 1500000071 97 | |
| 40450 | 69107 | 1500000077 | |
| 40600 | 09107 | 1500000072 | |
| 45120 | 7 | 1500000139 | |
| 45150 | 70630 | | |
| | | 1500000141 | |
| 45227 | 70631 | 1500000171 46 | |
| 45264 | 70940 | 1500000194 61 | |
| 5 | 71920 | 1500000363 | |
| | 71991 80 | 1500000364 | |
| 520854E | Q | 1500000465 44 | |
| 530201 | 8 | 1500000542 | |
| 530202 46 | 854181 | 1500000544 | |
| 530203 46 | 854183 | 1500000597 | |
| 530204 47 | 854185 71 | 1500000598 89 | |
| 530205 47 | 854186 71 | 1500000797 89 | |

| Notes | |
|-------|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |



Social Responsibility

We feel an obligation not only to corporate responsibility, but also to the well-being of people and the environment. To this, we devote resources, initiative, commitment and, last but not least, money.

Environmental Commitment

At Rothenberger, environmentally responsible business is a given. Therefore the company holds to the strictest environmental standards and is committed to responsible use of resources and energy.

Accepting Social Responsibility

Corporate social responsibility is more than just a nice phrase for us – it's a binding promise. Rothenberger accepts its social responsibility and regularly supports many projects and events for the common good. All German apprentices and trainees undergo, as part of their educational program, a social responsibility week involving care for the elderly, the sick or the disabled. The goal is to convey more to young people than just instructional material and knowledge. It is a conscious contribution to developing social competency among young employees.

TOOLS FOR LIFE Foundation

In 2008, Dr. Helmut Rothenberger founded the Tools for Life Foundation, which is committed to the sustainable common good of our society. The goal of Tools for Life is to help people on site, around the world, by establishing and improving drinking water and energy supplies. This is because potable water and a functional energy supply are still not common in many parts of the world. In the spirit of helping people to help themselves, Tools for Life inspires people to take their future into their own hands. Rothenberger is a committed partner, supporting the foundation with products and employee expertise to provide valuable assistance. Furthermore, Tools for Life collaborates with renowned international aid organizations.

Disclaimer

Due to continual technical development and modification of our products in line with customer requirements we reserve the right to alter the appearance, scope of delivery, performance data, features, dimensions and weights of our products without notice and without liability. We will not be held liable for modification to previously delivered products. We also reserve the right to remove products from our range. This catalogue replaces all previous editions. Declarations of technical standards are non-binding. Work instructions; and tips on product usage and safety; are non-binding and are in no way intended to replace legal norms or other regulations issued by professional organisations or statutory accident insurance funds in the respective country of use. No part of this catalogue may be reproduced, converted into a machine-readable format; or stored or processed in an electronic system by means of reprint, photocopy, microfilm or by any other method without the prior written permission of ROTHENBERGER Industrial GmbH. Modifications and additions to this catalogue are not permitted. All rights reserved for all jurisdictions.